



US010690277B2

(12) **United States Patent**
Fremont

(10) **Patent No.:** **US 10,690,277 B2**
(45) **Date of Patent:** **Jun. 23, 2020**

(54) **RADIO FREQUENCY IDENTIFICATION
SMART INSPECTION ASSURANCE CAP**

6,649,829 B2* 11/2003 Garber F16L 37/0841
137/177

(71) Applicant: **Jiffy-tite Co., Inc.**, Lancaster, NY (US)

7,061,382 B2 6/2006 Claessens et al.

7,298,274 B2 11/2007 Chen et al.

7,400,247 B2 7/2008 Hopman et al.

7,541,932 B2 6/2009 Lee et al.

7,696,886 B2 4/2010 Lai

7,839,288 B2 11/2010 Wang et al.

8,120,484 B2 2/2012 Chrisholm

8,297,661 B2* 10/2012 Proulx F16L 33/22
285/242

(72) Inventor: **Bradley C. Fremont**, Tonawanda, NY
(US)

(73) Assignee: **Oetiker NY, Inc.**, Lancaster, NY (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 345 days.

8,485,359 B2 7/2013 Anderson

9,107,820 B2 8/2015 Mintchev et al.

(Continued)

(21) Appl. No.: **15/460,837**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Mar. 16, 2017**

GB 2521857 A 7/2015

KR 100927464 B1 11/2009

(65) **Prior Publication Data**

US 2018/0266602 A1 Sep. 20, 2018

Primary Examiner — David Bochna

(74) *Attorney, Agent, or Firm* — Simpson & Simpson,
PLLC

(51) **Int. Cl.**

F16L 35/00 (2006.01)

F16L 37/098 (2006.01)

G06K 19/077 (2006.01)

G06K 19/07 (2006.01)

(57) **ABSTRACT**

A radio frequency identification (RFID) smart inspection assurance cap, including a body having a through-bore, an outer surface, and an inner surface and, an RFID circuit including an RFID chip a first circuit lead connected to the RFID chip, and a second circuit lead connected to the RFID chip, the first circuit lead and the second circuit lead electrically disconnected from one another, deactivating the RFID chip wherein the RFID smart inspection assurance cap is operatively arranged on a fluid connector, the first circuit lead is arranged to contact the fluid connector, the second circuit lead is arranged to contact the fluid connector, wherein the RFID circuit is completed when the first circuit lead and the second circuit lead simultaneously contact the fluid connector.

(52) **U.S. Cl.**

CPC **F16L 35/00** (2013.01); **F16L 37/0985**
(2013.01); **G06K 19/0716** (2013.01); **G06K**
19/07758 (2013.01); **F16L 2201/10** (2013.01)

(58) **Field of Classification Search**

CPC G06K 19/07758; G06K 19/0716; F16L
2201/10

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

5,604,681 A * 2/1997 Koeninger B67D 7/348
700/285

6,271,753 B1 8/2001 Shukla

20 Claims, 24 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,283,334 B2* 3/2016 Mantell A61M 13/00
2006/0076419 A1* 4/2006 Johnson F16L 33/30
235/492
2008/0073906 A1* 3/2008 Turner F16L 39/02
285/120.1
2008/0238675 A1 10/2008 Yang
2009/0137887 A1* 5/2009 Shariati A61B 5/0031
600/345
2010/0057296 A1* 3/2010 Ryman F16L 37/08
701/36
2010/0286467 A1* 11/2010 Pesach A61M 5/158
600/9
2012/0000858 A1 1/2012 Butler et al.
2015/0032253 A1 1/2015 O'Dougherty et al.
2015/0061282 A1* 3/2015 Faldt F16L 39/00
285/124.5
2015/0238673 A1* 8/2015 Gerber G06K 19/077
210/85
2016/0178101 A1* 6/2016 Blake F16L 37/0987
285/417
2016/0186906 A1* 6/2016 Blake F16L 37/098
285/319
2016/0229680 A1* 8/2016 Cornett F16L 55/1015
2016/0332452 A1* 11/2016 Begeal B41J 2/17546
2016/0369922 A1* 12/2016 Blake F16L 37/0987
2018/0073670 A1* 3/2018 Wolfgang F16L 37/096
2019/0049049 A1* 2/2019 Ignaczak G06K 19/0716

* cited by examiner




Fig. 1




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 4




Fig. 5




Fig. 6A




Fig. 6B




Fig. 7




Fig. 8




Fig. 9A




Fig. 9B




Fig. 10




Fig. 11




Fig. 12A




Fig. 12B




Fig. 13




Fig. 14




Fig. 15A




Fig. 15B




Fig. 16




Fig. 17A




Fig. 17B

1

RADIO FREQUENCY IDENTIFICATION SMART INSPECTION ASSURANCE CAP

FIELD

This disclosure relates generally to a fluid connector, and, more specifically, to a fluid connector including a radio frequency identification (RFID) chip arranged on or within an assurance cap to allow position testing of the cap with RFID detection means to reduce possible leak paths of the fluid connector.

BACKGROUND

Fluid connectors are integral components for many applications, and especially for automotive applications. Since an automotive system is made up of various components such as a radiator, transmission, and engine, fluid must be able to travel not only within each component but also between components. An example of fluid traveling between components is the transmission fluid traveling from the transmission to the transmission oil cooler in order to lower the temperature of the transmission fluid. Fluid predominantly moves between components via flexible or rigid hoses which connect to each component by fluid connectors.

When fluid connectors are secured to devices such as radiators, tubular connectors inserted into these fluid connectors may not be fully seated and allow leak paths to form once the assembly is pressurized. Current tubular connectors include a witness bead which is used as a visual indicator of proper sealing, but these witness beads are not always reliable as it is dependent on a human user to check.

In addition to a witness bead, an assurance cap may be used to further secure and verify the tubular connector is properly inserted into the fluid connector. The assurance cap is installed concentrically about the tubular connector and snaps over an outer circumference of the fluid connector. In some instances, the assurance cap may only partially secure to the fluid connector since these fluid connectors are typically installed in the confined spaces of an engine bay of an automobile. Moreover, a user may not be able to hear the audible "click" sound when the assurance cap fully secures to the fluid connector, leading to the tubular connector blowing out of the fluid connector since it was not fully installed.

Thus, there has been a long-felt need for an assurance cap which can be secured to a fluid connector which allows a user to positively ensure that the assurance cap is properly seated such that the tubular connector is secured within the fluid connector and that the assurance cap is secured to the fluid connector.

BRIEF SUMMARY

The present disclosure broadly includes a radio frequency identification (RFID) smart inspection assurance cap, including a body having a through-bore, an outer surface, and an inner surface and, an RFID circuit including an RFID chip, a first circuit lead connected to the RFID chip, and a second circuit lead connected to the RFID chip, the first circuit lead and the second circuit lead electrically disconnected from one another, deactivating the RFID chip

wherein the RFID smart inspection assurance cap is operatively arranged on a fluid connector, the first circuit lead is arranged to contact the fluid connector, the second circuit lead is arranged to contact the fluid connector,

2

wherein the RFID circuit is completed when the first circuit lead and the second circuit lead simultaneously contact the fluid connector.

Additionally, the present disclosure broadly includes a fluid connector assembly including a fluid connector having a through-bore, a tubular connector arranged in the through-bore of the fluid connector, and an RFID smart inspection assurance cap operatively arranged to connect to the fluid connector, the RFID smart inspection assurance cap including a body having a through-bore, an outer surface, and an inner surface and, an RFID circuit including an RFID chip a first circuit lead connected to the RFID chip, and a second circuit lead connected to the RFID chip, the first circuit lead and the second circuit lead electrically disconnected from one another, deactivating the RFID chip wherein the RFID smart inspection assurance cap is operatively arranged on a fluid connector, the first circuit lead is arranged to contact the fluid connector, the second circuit lead is arranged to contact the fluid connector, wherein the RFID circuit is completed when the first circuit lead and the second circuit lead simultaneously contact the fluid connector.

Even further, the present disclosure broadly includes an RFID smart inspection assurance cap, including a body having a through-bore axially arranged within the body, an outer surface, an inner surface, and an aperture arranged radially within the body, and a sensor ring arranged within the through-bore and in contact with the inner surface, the sensor ring comprising an RFID chip.

These and other objects, features and advantages of the present disclosure will become readily apparent upon a review of the following detailed description, in view of the drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The nature and mode of operation of the present disclosure will now be more fully described in the following detailed description of the disclosure taken with the accompanying figures, in which:

FIG. 1 is a perspective view of a fluid connector and a first example embodiment of an assurance cap assembly;

FIG. 2A is a front perspective view of the fluid connector;

FIG. 2B is a rear perspective view of the fluid connector;

FIG. 3A is a front perspective view of the first example embodiment of the assurance cap assembly;

FIG. 3B is a rear perspective view of the first example embodiment of the assurance cap assembly;

FIG. 4 is a cross-sectional view of the fluid connector and the first example embodiment of the assurance cap assembly taken generally along line 4-4 in FIG. 1;

FIG. 5 is a perspective view of a fluid connector and a second example embodiment of an assurance cap assembly;

FIG. 6A is a front perspective view of the second example embodiment of the assurance cap assembly;

FIG. 6B is a rear perspective view of the second example embodiment of the assurance cap assembly;

FIG. 7 is a cross-sectional view of the fluid connector and the second example embodiment of the assurance cap assembly taken generally along line 7-7 in FIG. 5;

FIG. 8 is a perspective view of a fluid connector and a third example embodiment of an assurance cap assembly;

FIG. 9A is a front perspective view of the third example embodiment of the assurance cap assembly;

FIG. 9B is a rear perspective view of the third example embodiment of the assurance cap assembly;

FIG. 10 is a cross-sectional view of the fluid connector and the third example embodiment of the assurance cap assembly taken generally along line 10-10 in FIG. 8;

FIG. 11 is a perspective view of a fluid connector and a fourth example embodiment of the assurance cap assembly;

FIG. 12A is a front perspective view of the fourth example embodiment of the assurance cap assembly;

FIG. 12B is a rear perspective view of the fourth example embodiment of the assurance cap assembly;

FIG. 13 is a cross-sectional view of the fluid connector and the fourth example embodiment of the assurance cap assembly taken generally along line 13-13 in FIG. 11;

FIG. 14 is a perspective view of a fluid connector and a fifth example embodiment of an assurance cap assembly;

FIG. 15A is a front perspective view of the fifth example embodiment of the assurance cap assembly;

FIG. 15B is a rear perspective view of the fifth example embodiment of the assurance cap assembly;

FIG. 16 is a perspective view of a sensor ring;

FIG. 17A is a cross-sectional view of the fluid connector and the fifth example embodiment of the assurance cap assembly not fully seated on the fluid connector taken generally along line 17-17 in FIG. 14; and,

FIG. 17B is a cross-sectional view of the fluid connector and the fifth example embodiment of the assurance cap assembly fully seated on the fluid connector taken generally along line 17-17 in FIG. 14.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the disclosure. It is to be understood that this disclosure is not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and, as such, may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the claims.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure pertains.

Furthermore, as used herein, “and/or” is intended to mean a grammatical conjunction used to indicate that one or more of the elements or conditions recited may be included or occur. For example, a device comprising a first element, a second element and/or a third element, is intended to be construed as any one of the following structural arrangements: a device comprising a first element; a device comprising a second element; a device comprising a third element; a device comprising a first element and a second element; a device comprising a first element and a third element; a device comprising a first element, a second element and a third element; or, a device comprising a second element and a third element.

Adverting now to the figures, FIG. 1 is a perspective view of fluid connector 100 and a first example embodiment of assurance cap assembly 200. Assurance cap assembly 200 secures to fluid connector 100 on section 101 (shown in FIG. 2). Section 102 of fluid connector 100 comprises threads 104 which allow fluid connector 100 to secure to an apparatus such as a transmission, radiator, oil cooler, etc. Fluid connector 100 also includes head 110 which allows a user to use a tool such as a wrench to screw fluid connector 100 into a

corresponding apparatus (not shown). Through-bore 103 (shown in FIG. 2) is arranged in the center of fluid connector 100 and passes through the whole body of fluid connector 100.

FIG. 2A and FIG. 2B are a front perspective view and a rear perspective view, respectively, of fluid connector 100. Fluid connector 100 comprises section 101 and section 102. Section 101 includes snap ring 106, outer surface 108, inner surface 112, shoulder 113, shoulder surface 114, shoulder 116, and channel 118. Snap ring 106 is arranged within apertures 107 of fluid connector 100 and secures tubular connector 800 (shown in FIG. 4) within through-bore 103 of fluid connector 100.

FIG. 3A and FIG. 3B are a front perspective view and a rear perspective view, respectively, of the first example embodiment of assurance cap assembly 200. Assurance cap assembly 200 broadly comprises body 201, channel 202, through-bore 204, lips 205, arms 206, tabs 207, sensor arm 210, surface 211, and sensor circuit 300. Channel 202 is arranged to allow tubular connector 800 (shown in FIG. 4) and a hose to be concentrically arranged within body 201. Tubular connector 800 (shown in FIG. 4) is arranged within channel 202 and then pressed into through-bore 204, deforming lips 205. Once tubular connector 800 (shown in FIG. 4) is arranged within through-bore 204, lips 205 return to their original position to further secure tubular connector 800 within through-bore 204. Arms 206 extend axially from body 201 and are operatively arranged to secure assurance cap assembly 200 to fluid connector 100. Tabs 207 are operatively arranged on the distal ends of arms 206. The geometry of arms 206 and tabs 207 allow for tabs 207 to deform around shoulder 116 and secure within channel 118 of fluid connector 100. This interaction between channel 118 and tabs 207 secure assurance cap assembly 200 to fluid connector 100. Sensor arm 210 houses sensor circuit 300, with sensor circuit 300 embedded within sensor arm 210. Sensor arm 210 is shown as a cutaway in order to improve clarity of sensor circuit 300. Sensor circuit 300 comprises circuit leads 302, RFID chip 304, and antenna 306. Circuit leads 302 axially extend and protrude from surface 211 of sensor arm 210. Additionally, circuit leads 302 are operatively arranged to not engage one another in such a way which would complete and allow electricity to flow through sensor circuit 300.

FIG. 4 is a cross-sectional view of fluid connector 100 and the first example embodiment of assurance cap assembly 200 taken generally along line 4-4 in FIG. 1. As shown in the figure, sensor circuit 300 only activates when circuit leads 302 are in contact with fluid connector 100. In an example embodiment, fluid connector 100 is made of an electrical conducting material such as metal. However, it should be appreciated that fluid connector 100 only requires an electrical conducting section to complete sensor circuit 300. The electrical conducting section only needs to be arranged on fluid connector 100 in such a way as to allow circuit leads 302 to complete sensor circuit 300. An example of an electrical conducting section of fluid connector 100 comprises head 110 made of an electrical conducting material, while the remainder of fluid connector 100 is made of a non-conducting material such as plastic. In order for circuit leads 302 to reach fluid connector 100, tabs 207 must be arranged within channel 118. If tabs 207 are not arranged within channel 118, assurance cap assembly 200 is not properly seated on fluid connector 100. If assurance cap assembly 200 is not properly seated on fluid connector 100, then sensor circuit 300 will not be completed and RFID chip 304 will be unable to be scanned by an RFID reader by a

technician during installation of assurance cap assembly 200. This lack of a reading is an indication to the technician that assurance cap assembly 200 is not properly seated on fluid connector 100 and must be reset. The completion of sensor circuit 300 due to the contact of circuit leads 302 with fluid connector 100 is due to the geometry of shoulder 116, channel 118, arms 206, tabs 207, sensor arm 210 and sensor circuit 300. Tubular connector 800 is represented in FIG. 4 as a dashed outline for clarity. It should be understood that tubular connector 800 is a solid body arranged within the assembly. Additionally, it should be understood that tubular connector 800 is arranged in each and every embodiment of an assurance cap assembly contained within this disclosure.

FIG. 5 is a perspective view of fluid connector 100 and a second example embodiment of assurance cap assembly 200. The second example embodiment of assurance cap assembly 200 is structurally substantially identical to the first example embodiment of assurance cap assembly 200 except for the sensor which is placed on the assurance cap assembly. The second example embodiment of assurance cap assembly 200 includes sensor circuit 400. Sensor circuit 400 comprises circuit leads 402, RFID chip 404, and antenna 406. Circuit leads 402 axially extend and protrude from sensor arm 220. Additionally, circuit leads 402 are operatively arranged to not engage one another in such a way which would complete sensor circuit 400 and allow electricity to flow through sensor circuit 400.

FIG. 6A and FIG. 6B are a front perspective view and a rear perspective view, respectively, of the second example embodiment of assurance cap assembly 200. Sensor circuit 400 is operatively arranged on surface 221 of sensor arm 220. In an example embodiment, sensor circuit 400 is arranged on a substrate prior to being placed on sensor arm 220, similar to a sticker or the like. However, it should be appreciated that sensor circuit 400 can be integral with sensor arm 220 or arranged directly on surface 221 of sensor arm 220.

FIG. 7 is a cross-sectional view of fluid connector 100 and the second example embodiment of assurance cap assembly 200 taken generally along line 7-7 in FIG. 5. As shown in the figure, sensor circuit 400 only activates when circuit leads 402 are in contact with fluid connector 100. In an example embodiment, fluid connector 100 is made of an electrical conducting material such as metal. However, it should be appreciated that fluid connector 100 only requires an electrical conducting section to complete sensor circuit 400. The electrical conducting section only needs to be arranged on fluid connector 100 in such a way as to allow circuit leads 402 to complete sensor circuit 400. An example of an electrical conducting section of fluid connector 100 comprises head 110 made of an electrical conducting material while the remainder of fluid connector 100 is made of a non-conducting material, such as plastic. In order for circuit leads 402 to reach fluid connector 100, tabs 207 must be arranged within channel 118. If tabs 207 are not arranged within channel 118, assurance cap assembly 200 is not properly seated on fluid connector 100. If assurance cap assembly 200 is not properly seated on fluid connector 100, then sensor circuit 400 will not be completed and RFID chip 404 will be unable to be scanned by an RFID reader by a technician during installation of assurance cap assembly 200. This lack of a reading is an indication to the technician that assurance cap assembly 200 is not properly seated on fluid connector 100 and must be reset. The completion of sensor circuit 400 due to the contact of circuit leads 402 with

fluid connector 100 is due to the geometry of shoulder 116, channel 118, arms 206, tabs 207, sensor arm 220 and sensor circuit 400.

FIG. 8 is a perspective view of fluid connector 100 and a third example embodiment of assurance cap assembly 500.

FIG. 9A and FIG. 9B are a front perspective view and a rear perspective view, respectively, of the third example embodiment of assurance cap assembly 500. Assurance cap assembly 500 broadly includes body 501, tabs 502, surface 503, through-bore 504, edge 506, tab 507, and sensor circuit 400. Tabs 502 further secure tubular connector 800 and/or hose concentrically within through-bore 504. Sensor circuit 400 is operatively arranged on surface 503 of body 501. In an example embodiment, sensor circuit 400 is arranged on a substrate prior to being placed on surface 503, similar to a sticker or the like. However, it should be appreciated that sensor circuit 400 can be integral with body 501 or arranged directly on surface 503 of body 501.

FIG. 10 is a cross-sectional view of fluid connector 100 and the third example embodiment of assurance cap assembly 500 taken generally along line 10-10 in FIG. 8. Assurance cap assembly 500 secures to fluid connector 100 via tab 507 operatively arranged on edge 506. Tab 507 extends radially inward and secures within channel 118 of fluid connector 100. Assurance cap assembly 500 is manufactured from a material which allows tab 507 to deform enough to move past shoulder 116 of fluid connector 100 when assurance cap assembly 500 is assembled on fluid connector 100. As shown in the figure, sensor circuit 400 only activates when circuit leads 402 are in contact with fluid connector 100. In order for circuit leads 402 to reach fluid connector 100, tab 507 must be arranged within channel 118. If tab 507 is not arranged within channel 118, assurance cap assembly 500 is not properly seated on fluid connector 100. If assurance cap assembly 500 is not properly seated on fluid connector 100, then sensor circuit 400 will not be completed and will be unable to be scanned by an RFID reader by a technician during installation of assurance cap assembly 500. This lack of a reading is an indication to the technician that assurance cap assembly 500 is not properly seated on fluid connector 100 and must be reset. The completion of sensor circuit 400 due to the contact of circuit leads 402 with fluid connector 100 is due to the geometry of shoulder 116, channel 118, edge 506, tab 507, and sensor circuit 400.

FIG. 11 is a perspective view of fluid connector 100 and a fourth example embodiment of assurance cap assembly 500. The fourth example embodiment of assurance cap assembly 500 is structurally substantially identical to the third example embodiment of assurance cap assembly 500 except for the sensor which is placed on the assurance cap assembly. The fourth example embodiment of assurance cap assembly 500 includes sensor circuit 300.

FIG. 12A and FIG. 12B are a front perspective view and a rear perspective view, respectively, of the fourth example embodiment of assurance cap assembly 500. Surface 503 is shown as a cutaway in order to improve clarity of sensor circuit 300. Sensor circuit 300 comprises circuit leads 302, RFID chip 304, and antenna 306. Circuit leads 302 axially extend and protrude from edge 506 of body 501. Additionally, circuit leads 302 are operatively arranged to not engage one another in such a way which would complete sensor circuit 300 and allow electricity to flow through sensor circuit 300.

FIG. 13 is a cross-sectional view of fluid connector 100 and the fourth example embodiment of assurance cap assembly 500 taken generally along line 13-13 in FIG. 11. As shown in the figure, sensor circuit 300 only activates when

circuit leads **302** are in contact with fluid connector **100**. The electrical conducting section only needs to be arranged on fluid connector **100** in such a way as to allow circuit leads **302** to complete sensor circuit **300**. In order for circuit leads **302** to reach fluid connector **100**, tab **507** must be arranged within channel **118**. If tabs **507** are not arranged within channel **118**, assurance cap assembly **500** is not properly seated on fluid connector **100**. If assurance cap assembly **500** is not properly seated on fluid connector **100**, then sensor circuit **300** will not be completed and RFID chip **304** will be unable to be scanned by an RFID reader by a technician during installation of assurance cap assembly **500**. This lack of a reading is an indication to the technician that assurance cap assembly **500** is not properly seated on fluid connector **100** and must be reset. The completion of sensor circuit **400** due to the contact of circuit leads **302** with fluid connector **100** is due to the geometry of shoulder **116**, channel **118**, edge **506**, tab **507**, and sensor circuit **300**.

FIG. **14** is a perspective view of fluid connector **100** and a fifth example embodiment of assurance cap assembly **600**. The fifth example embodiment of assurance cap assembly **600** is structurally substantially identical to the third example embodiment of assurance cap assembly **500** except for addition of apertures **605** and the sensor which is corresponding to the assurance cap assembly. The fifth example embodiment of assurance cap assembly **600** includes sensor ring **700** operatively arranged in through-bore **604** of assurance cap assembly **600**.

FIG. **15A** and FIG. **15B** are a front perspective view and a rear perspective view, respectively, of the fifth example embodiment of assurance cap assembly **600**. Assurance cap assembly **600** broadly includes body **601**, tabs **602**, surface **603**, through-bore **604**, apertures **605**, edge **606**, tab **607**, and sensor ring **700**. Tabs **602** further secure tubular connector **800** and/or a hose concentrically within through-bore **604**. Sensor ring **700** is slidably arranged on surface **608** of body **601**. Tab **607** extends radially inward from edge **606** and secures within channel **118** of fluid connector **110** (shown in FIG. **17B**) when assurance cap assembly **600** is properly seated on fluid connector **100**.

FIG. **16** is a perspective view of sensor ring **700**. Sensor ring **700** broadly includes body **701**, sensor circuit **702**, channel **704**, and shoulders **706**. Sensor circuit **702** includes RFID chip **708** and antenna **710**. Unlike the previous assurance cap example embodiments, sensor circuit **702** is a completed and connected RFID circuit which allows for scanning of sensor circuit **702** with an RFID scanner.

FIG. **17A** is a cross-sectional view of fluid connector **100** and the fifth example embodiment of assurance cap assembly **600** not fully seated on fluid connector **100** taken generally along line 17-17 in FIG. **14**. When body **601** is not fully seated on fluid connector **100**, sensor ring **700** is axially displaced from apertures **605**. In an example embodiment, fluid connector **100** is manufactured from a metallic material which prevents the transfer of electromagnetic waves through its body. However, it should be appreciated that any material which sufficiently blocks electromagnetic waves can be used to manufacture fluid connector **100**. Due to this electromagnetic signal blockage by fluid connector **100**, sensor circuit **702** of sensor ring **700** cannot be scanned by a technician, giving the technician notice that assurance cap assembly **600** is not fully seated on fluid connector **100** and must be reset.

FIG. **17B** is a cross-sectional view of fluid connector **100** and the fifth example embodiment of assurance cap assembly **600** fully seated on fluid connector **100** taken generally along line 17-17 in FIG. **14**. Once assurance cap assembly

is placed on fluid connector **100**, a technician then axially slides assurance cap assembly **600** towards fluid connector **100**. This sliding motion causes one of shoulders **706** of sensor ring **700** to abut against surface **114** of shoulder **113** of fluid connector **100**. This interaction between shoulder **113** and shoulder **706** causes sensor ring **700** to axially remain in place as body **601** is axially displaced towards fluid connector **100**. In a final assembled state, sensor ring **700** is axially aligned with apertures **605** to allow sensor circuit to interact with an RFID scanner. Apertures **605** allow for electromagnetic waves to reach sensor circuit **702** once sensor ring is in the correct axial position. Once sensor ring **700** is in the correct axial position and sensor ring **702** can be scanned, this indicates to a technician that assurance cap assembly **600** is fully seated on fluid connector **100**.

In the foregoing description, example embodiments are described. The specification and drawings are accordingly to be regarded in an illustrative rather than a restrictive sense.

It will be appreciated that various aspects of the above-disclosed disclosure and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

LIST OF REFERENCE NUMERALS

100	Fluid connector
101	Section
102	Section
103	Through-bore
104	Threads
106	Snap ring
107	Aperture
108	Outer surface
110	Head
112	Inner surface
113	Shoulder
114	Surface
116	Shoulder
118	Surface
200	Assurance cap assembly
201	Body
202	Channel
204	Through-bore
205	Lips
206	Arms
207	Tabs
210	Sensor arm
211	Surface
220	Sensor arm
221	Surface
300	Sensor circuit
302	Circuit leads
304	Radio frequency identification (RFID) chip
306	Antenna
400	Sensor circuit
402	Circuit leads
404	Radio frequency identification (RFID) chip
406	Antenna
500	Assurance cap assembly
501	Body
502	Tabs
503	Surface
504	Through-bore

- 506 Edge
- 507 Tab
- 600 Assurance cap assembly
- 601 Body
- 602 Tabs
- 603 Surface
- 604 Through-bore
- 605 Apertures
- 606 Edge
- 607 Tab
- 608 Surface
- 700 Sensor ring
- 701 Body
- 702 Sensor circuit
- 702A Radio frequency identification (RFID) chip
- 702B Antenna
- 704 Channel
- 706 Shoulders
- 708 surface Radio frequency identification (RFID) chip
- 710 Antenna
- 712 Surface
- 800 Tubular connector

What is claimed is:

1. A radio frequency identification (RFID) smart inspection assurance cap operatively arranged to communicate whether a tubular connector is fully seated in a fluid connector, comprising:

- a body comprising:
 - a through-bore;
 - radially outward facing surface; and,
 - an inner surface; and,
- a RFID circuit comprising:
 - a RFID chip;
 - a first circuit lead connected to said RFID chip; and,
 - a second circuit lead connected to said RFID chip, said first circuit lead and said second circuit lead electrically disconnected from one another, deactivating said RFID chip;

wherein:

- said RFID smart inspection assurance cap is operatively arranged to connect to said fluid connector;
- said first circuit lead is arranged to contact said fluid connector;
- said second circuit lead is arranged to contact said fluid connector; and,
- said RFID circuit is completed when said first circuit lead and said second circuit lead simultaneously contact said fluid connector.

2. The RFID smart inspection assurance cap as recited in claim 1, wherein said RFID circuit is embedded within said body of said assurance cap.

3. The RFID smart inspection assurance cap as recited in claim 1, wherein said RFID circuit is arranged on said radially outward facing surface of said body of said assurance cap.

4. The RFID smart inspection assurance cap as recited in claim 1, wherein said fluid connector comprises an electrical conducting section to complete said RFID circuit.

5. The RFID smart inspection assurance cap as recited in claim 1, wherein said fluid connector is made of an electrical conducting material.

6. The RFID smart inspection assurance cap as recited in claim 1, wherein said RFID smart inspection assurance cap is fully seated on said fluid connector when said first circuit lead and said second circuit lead contact said fluid connector.

7. The RFID smart inspection assurance cap as recited in claim 1, wherein said RFID chip activates when said RFID smart inspection assurance cap is fully seated on said fluid connector.

- 5 8. A fluid connector assembly, comprising:
 - a fluid connector comprising a first through-bore;
 - a tubular connector arranged in said first through-bore; and,
 - a radio frequency identification (RFID) smart inspection assurance cap operatively arranged to connect to said fluid connector and communicate whether the tubular connector is fully seated in the fluid connector, the RFID smart inspection assurance cap, comprising:
 - 10 a body comprising:
 - a second through-bore;
 - a radially outward facing surface; and,
 - an inner surface; and,
 - a RFID circuit comprising:
 - 15 a RFID chip;
 - a first circuit lead connected to said RFID chip; and,
 - a second circuit lead connected to said RFID chip, said first circuit lead and said second circuit lead electrically disconnected from one another, deactivating said RFID chip;

wherein:

- said RFID smart inspection assurance cap is operatively arranged on said tubular connector;
- said first circuit lead is arranged to contact said fluid connector;
- said second circuit lead is arranged to contact said fluid connector; and,
- said RFID circuit is completed when said first circuit lead and said second circuit lead simultaneously contact said fluid connector.

9. The RFID smart inspection assurance cap as recited in claim 8, wherein said RFID circuit is embedded within said body of said assurance cap.

10. The RFID smart inspection assurance cap as recited in claim 8, wherein said RFID circuit is arranged on said outer radially outward facing surface of said body of said assurance cap.

11. The RFID smart inspection assurance cap as recited in claim 8, wherein said fluid connector comprises an electrical conducting section to complete said RFID circuit.

12. The RFID smart inspection assurance cap as recited in claim 8, wherein said fluid connector is made of an electrical conducting material.

13. The RFID smart inspection assurance cap as recited in claim 8, wherein said RFID smart inspection assurance cap is fully seated on said fluid connector when said first circuit lead and said second circuit lead contact said fluid connector.

14. A radio frequency identification (RFID) smart inspection assurance cap, comprising:

- a body comprising:
 - a through-bore axially arranged within said body;
 - an inner surface formed by said through-bore; and,
 - an aperture arranged within said body, the aperture extending radially outward from the through-bore to a radially outward facing surface of said body; and,
 - a sensor ring slidably arranged within said through-bore and in contact with said inner surface.

15. The RFID smart inspection assurance cap as recited in claim 14, wherein said sensor ring comprises a RFID chip.

16. The RFID smart inspection assurance cap as recited in claim 15, wherein in a first state, said RFID chip is prevented from communication by said body.

17. The RFID smart inspection assurance cap as recited in claim 16, wherein in a second state, said sensor ring is operatively arranged to allow communication of said RFID chip via said aperture.

18. The RFID smart inspection assurance cap as recited in claim 17, wherein said RFID smart inspection assurance cap is fully seated on said fluid connector when said sensor ring is in said second state.

19. The RFID smart inspection assurance cap as recited in claim 15, further comprising a tubular connector arranged within said through-bore.

20. The RFID smart inspection assurance cap as recited in claim 14, wherein said RFID smart inspection assurance cap is operatively arranged to connect to a fluid connector.

* * * * *