



US010751558B2

(12) **United States Patent**
Young

(10) **Patent No.:** **US 10,751,558 B2**
(45) **Date of Patent:** **Aug. 25, 2020**

(54) **UNIVERSAL NOZZLE CONNECTOR WITH AN ADJUSTABLE MOUNT**

F16L 3/24; F16L 3/00; F16L 3/08; F16L 3/1083; F16L 3/221; F16L 3/127; F16L 3/1066; F16L 3/233; F16L 3/14; F16L 3/137; F16L 23/06; F16L 33/12;
(Continued)

(71) Applicant: **Performance Advantage Company, Inc.**, Lancaster, NY (US)

(72) Inventor: **Richard E. Young**, Lancaster, NY (US)

(56)

References Cited

(73) Assignee: **Performance Advantage Company, Inc.**, Lancaster, NY (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

196,807 A * 11/1877 Jolliffe F16L 23/06
285/409
455,967 A * 7/1891 Lusk et al. F16L 33/12
24/271

(Continued)

(21) Appl. No.: **15/991,151**

FOREIGN PATENT DOCUMENTS

(22) Filed: **May 29, 2018**

DE 10258828 A1 7/2004
WO 2006043738 A1 4/2006

(65) **Prior Publication Data**

US 2018/0272168 A1 Sep. 27, 2018

Related U.S. Application Data

OTHER PUBLICATIONS

(63) Continuation of application No. 14/598,663, filed on Jan. 16, 2015, now abandoned.

U.S. Statutory Invention Registration No. H1012, Published Jan. 7, 1992 (Senatro).

(Continued)

Primary Examiner — Hiwot E Tefera

Assistant Examiner — Taylor L Morris

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(51) **Int. Cl.**
A62C 31/28 (2006.01)
F16L 23/06 (2006.01)

(Continued)

(57) **ABSTRACT**


(52) **U.S. Cl.**
CPC *A62C 31/28* (2013.01); *A62C 31/24* (2013.01); *F16L 3/233* (2013.01); *F16L 23/06* (2013.01);

(Continued)

An adjustable locking assembly, including a strap lock including a clamping element, a locking strap including a first end connected to the strap lock and a second end connected to a locking pin, and a pin locking element including a pivoting latch, the pivoting latch including a channel arranged to receive the locking pin, wherein in a locked position, the locking pin is secured in the channel and the pivoting latch is pivoted away from the strap lock, and in an unlocked position, the locking strap is freely movable.

(58) **Field of Classification Search**
CPC ... B05B 15/061; B05B 15/064; B05B 7/1481; F16L 3/1033; F16L 3/1041; F16L 3/13;

15 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,124,935	A	9/2000	Matthews	7,931,310	B2 *	4/2011	Lake	F16L 17/025 285/111
6,234,277	B1	5/2001	Kaczmarek	3,020,895	A1	9/2011	Reichmuth	
6,305,995	B1	10/2001	Stauning et al.	8,132,764	B2 *	3/2012	Kuipers	B62J 6/02 24/273
6,364,262	B1	4/2002	Gibson et al.	8,177,146	B2	5/2012	Chen	
6,378,823	B1 *	4/2002	Edholm	8,186,643	B2 *	5/2012	Luo	F16L 41/008 248/230.8
		 B60K 15/067	8,348,317	B1	1/2013	Bird	
			180/68.5	8,398,040	B2 *	3/2013	Busch	A62B 9/04 248/230.1
6,402,198	B2 *	6/2002	Gollungberg	8,413,933	B2 *	4/2013	Benne	F16L 3/11 248/62
		 B60K 15/067					
			280/830	8,534,614	B2	9/2013	Guthke et al.	
6,473,945	B1 *	11/2002	Draper	8,770,537	B2	7/2014	Go	
		 F16L 23/06	8,882,066	B2 *	11/2014	Otten	B65D 63/00 248/230.8
			24/270	8,960,617	B2 *	2/2015	Karlsson	B60K 15/067 248/222.14
6,561,396	B2 *	5/2003	Ketterhagen	9,127,807	B1 *	9/2015	Holloway	F16M 13/022
		 B60R 9/042	9,303,792	B2 *	4/2016	Heims	H02G 3/32
			224/310	9,447,899	B2	9/2016	Minami	
6,896,318	B2 *	5/2005	Marrs	9,909,535	B2 *	3/2018	Sirosh	F02M 21/0221
		 B62D 27/02	10,022,574	B2 *	7/2018	McLoughlin	A62C 31/05
			280/833	10,288,195	B2 *	5/2019	Crouzy	F16L 3/233 24/16 PB
6,932,303	B2 *	8/2005	Snyder					
		 F16L 3/04					
			248/58					
6,971,826	B2 *	12/2005	Valentine					
		 B60P 7/12					
			410/104					
6,994,300	B2	2/2006	Labeirie et al.	2006/0006648	A1	1/2006	Grimmett et al.	
7,114,686	B2	10/2006	Andrigo	2006/0131465	A1 *	6/2006	Lynch, Jr.	F16L 3/2235 248/68.1
7,128,345	B2	10/2006	Bartholomä et al.					
7,261,256	B2 *	8/2007	Pattie	2007/0040075	A1	2/2007	Moretto	
		 F16L 3/233	2007/0257159	A1 *	11/2007	Nelson	F16B 21/02 248/73
			244/129.1					
7,300,210	B2 *	11/2007	Johnson	2009/0065659	A1	3/2009	Dann	
		 F16C 35/063	2009/0114784	A1 *	5/2009	Tam	B60K 15/067 248/205.1
			384/537					
7,402,074	B2	7/2008	LeBlanc et al.	2010/0219301	A1	9/2010	Sampson	
7,434,958	B2	10/2008	Yang et al.	2012/0145839	A1	6/2012	Runels et al.	
7,445,252	B2 *	11/2008	Ho	2013/0256471	A1	10/2013	Ruiz et al.	
		 F16L 23/06	2016/0076430	A1 *	3/2016	Freeman	F01N 3/2066 60/301
			285/407					
7,461,823	B2 *	12/2008	Decker	2016/0082829	A1 *	3/2016	Hummel	F16B 2/08 248/315
		 E04F 10/0644					
			248/230.8	2019/0014924	A1 *	1/2019	Penalver, Jr.	A47B 96/1441
7,516,922	B1	4/2009	Kirschner	2019/0092439	A1 *	3/2019	Stella	B63C 11/22
7,520,478	B2	4/2009	Whitfield					
7,540,071	B2	6/2009	Sampson					
7,546,986	B2	6/2009	Kim					
7,581,292	B2	9/2009	Votel					
7,621,487	B2 *	11/2009	Brown					
		 F16L 3/24					
			248/65					
7,861,981	B2 *	1/2011	Olver					
		 F16L 3/137					
			24/16 PB					
7,926,766	B2	4/2011	Tjerrild					

* cited by examiner




Fig. 1




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 4D




Fig. 4E




Fig. 4F




Fig. 5A




Fig. 5B




Fig. 5C





Fig. 5D






Fig. 7A




Fig. 7B




Fig. 7C




Fig. 8A







Fig. 8B



UNIVERSAL NOZZLE CONNECTOR WITH AN ADJUSTABLE MOUNT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is filed under 35 U.S.C. § 120 as a continuation patent application of U.S. patent application Ser. No. 14/598,663, filed on Jan. 16, 2015, which application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application No. 61/936,615, filed Feb. 6, 2014, which applications are incorporated herein by reference in their entireties.

FIELD

The present disclosure relates generally to an adjustable mounting system, and, more specifically, to an adjustable mounting system for a nozzle.

BACKGROUND

The most common firefighting nozzle has a 1.5" diameter nozzle in accordance with National Fire Protection Association (NFPA) Specifications. There are a number of manufacturers of 1.5" diameter nozzles. However, there are variances between nozzles from different manufacturers and thus there currently exists many different types of these nozzles. For example, some nozzles are very simple while some are very complex, and some are light in weight while others are quite heavy.

Fire trucks generally carry a number of different types of 1.5" nozzles. For example, some nozzles are pre-connected to a 1.5" hose that is pre-connected to the appropriate discharge. However, mounting pre-connected nozzles presents a significant challenge. A pre-connected nozzle ensures that a 1.5" hose is usually the first hose on the fire. The 1.5" pre-connect hose is usually a "cross lay hose bed" on top of the fire truck. In some cases, the 1.5" nozzle is carried in the hose bed. This could be located seven feet or more off the ground, thereby requiring a fire fighter to climb on the running board of the fire truck to reach the line. This can be dangerous, e.g., in bad weather conditions, resulting in falls.

Due to the popularity of 1.5" pre-connects, there are often multiple pre-connects. In order to minimize confusion, the control valves may have various color combinations on the pump panel with colored stripes on the fire hose that match the color for that hose on the pump control. The NFPA has described how these colors help to easily identify each pre-connect. However, it is often difficult and expensive to buy custom colored fire hose.

Some nozzles are not pre-connected, but are stored in an equipment compartment on tool boards or shelves, for example, while screwed into a screw plate which is a threaded male fitted base. The storage compartment is often congested and it may be difficult to mount nozzles either horizontally or vertically. There are also mounts that are "Tri Lock" spring action mounts in which three sets of teeth lock into the swivel female threads (internal threads) of the nozzle. Often, these sharp teeth can cause serious damage to the female threads causing significant and expensive damage. Mounting on a screw plate makes it difficult to turn the swivel by hand onto the screw plate, especially because it must be tightly screwed for it to be stable. Further, there commonly exists violent shaking of a truck on a rough road so stability is important.

A possible solution to this problem is disclosed in U.S. Pat. No. 8,020,895 (Reichmuth). Reichmuth discloses a pipe clamp and mounting structure that mounts a pipe to a fastening body. The device uses a holder which secures to the fastening body and a clamp that interlocks within the holder. The pipe that is mounted by the device has ribs corresponding to grooves cut into the holder which secure the pipe to the holder. The pipe can also be secured to the fastening body by resting in the holder and having the clamp lock around the pipe, fitting into a channel positioned between two ribs on the pipe. However, Reichmuth fails to disclose a mounting structure that can not only mount pipes, but be manipulated to secure other equipment such as boxes or cylindrical vessels. Additionally, Reichmuth fails to disclose a corresponding flexible mount module to further support the pipe that can be adjusted to accommodate a pipe with a larger or smaller diameter when compared to the size of the pipe secured within the mounting structure. Moreover, Reichmuth fails to disclose a strap that can be adjusted to have a greater tension if external forces act on the pipe and possibly cause the pipe to become unsecured.

Another possible solution to this problem is disclosed in U.S. Pat. No. 7,581,292 (Votel). Votel discloses a clip comprising opposed arms in mechanical communication with jaw members biased in a contacting relation. The jaw members are forced apart by a user applying opposing forces to each of the arms. The jaw members operably grasp the article when the arms are released. The clip has a structure for detachably interlocking with another clip. The clip may be made from a resilient material and includes a base structure defining an aperture and a gap, which enable the detachable interlinking. However, Votel fails to disclose a method for adjusting the distance between the two jaw members to accommodate larger objects which require securing. Additionally, Votel fails to disclose an adjustable locking assembly further comprising an adjustable strap to ensure an object is secured along its length.

Even further, another possible solution to this problem is disclosed in U.S. Pat. No. 4,960,063 (Bontemps). Bontemps discloses a safety device for the foot-holder of a sailboard or the like in which the foot-holder has a strap fixed at one end on the sailboard and another end secured to a latch which can be engaged in a locking body. The latch and locking body are arranged so that under a force exerted on the latch in a certain direction, the latch is unlocked to enlarge the loop while remaining engaged in the locking body. Under a stress exerted on the latch in a second direction, the latch is released from the locking body and opens the loop. However, Bontemps fails to disclose a means of adjusting the distance between the fixed end and the latch end of the strap. Instead, both ends of the strap are secured and only the length of the strap can be adjusted. Additionally, Bontemps fail to disclose a corresponding flexible mount module to further support the object that is locked within the strap. Moreover, Bontemps fails to disclose a locking module which would secure a universal nozzle connector.

Therefore, there is a long-felt need for an apparatus for storing non pre-connected nozzles to increase the speed of mounting and dismounting, while also increasing the storage stability. Further, there is also a long-felt need for a mounting system that will accommodate a pre-connected nozzle at a height level easily reached by a user while standing on the ground and that is arranged to accommodate a variety of nozzle sizes.

SUMMARY

According to aspects illustrated herein, there is provided an adjustable locking assembly, comprising a strap lock

including a clamping element, a locking strap including a first end connected to the strap lock and a second end connected to a locking pin, and a pin locking element including a pivoting latch, the pivoting latch including a channel arranged to receive the locking pin, wherein in a locked position, the locking pin is secured in the channel and the pivoting latch is pivoted away from the strap lock, and in an unlocked position, the locking strap is freely movable.

According to aspects illustrated herein, there is provided a mounting assembly for a nozzle, the nozzle comprising an inlet end, a discharge end and a universal connector adapted to connect to the inlet end of the nozzle, the universal connector comprising a hollow cylindrical body having a first end with internal threading, and a second end, an externally threaded cylinder protruding from the second end and a rim circumscribing the hollow cylindrical body between the first end and the second end, the mounting assembly comprising a track, a connector base connected to the track, the connector base including a channel arranged to support the universal connector, an adjustable locking assembly, including a strap lock including a clamping element, a locking strap including a first end connected to the strap lock and a second end connected to a locking pin, and a pin locking element including a pivoting latch, the pivoting latch including a channel arranged to receive the locking pin, wherein in a locked position, the locking pin is secured in the channel and the pivoting latch is pivoted away from the strap lock, and in an unlocked position, the locking strap is freely movable, and a flexible mount assembly connected to the track and arranged to support the discharge end of the nozzle.

The present disclosure comprises a flexible mount assembly adapted to support a discharge end of a nozzle, the flexible mount assembly comprising a first mount comprising a first rear surface and a first front surface, a first arm extending upwardly from the first mount, the first arm comprising a first extended portion extending from the first arm and, a first base extending outwardly from the first front surface adapted to connect to a track and, a second mount comprising a second rear surface and a second front surface, a second arm extending upwardly from the second mount, the second arm comprising a second extended portion extending from the second arm and, a second base extending outwardly from the second front surface adapted to connect to the track, wherein the first rear surface is in contact with the second rear surface.

The present disclosure also comprises a storage mount for a universal connector, comprising a base comprising a curved end, a flexible plank, a tab extending upwardly from the plank arranged to act as a radial barrier to the universal connector, a curved wall extending upwardly from the curved end of the base which partially secures the universal connector concentrically within the curved wall and, wherein the tab is displaced downwardly when the plank is pressed downward to retrieve or insert the universal connector.

The present disclosure also comprises an adjustable locking assembly, comprising a strap lock comprising a clamping element, a locking strap secured to the strap lock, the locking strap comprising a locking pin and, a pin locking element comprising a pivoting latch with a channel, the pivoting latch comprising a locked position, wherein the channel of the pivoting latch is adapted to receive the locking pin at a distance away from the strap lock, and the locking strap is freely movable when the pivoting latch is in a position other than the locked position.

The present disclosure also comprises a universal connector, comprising a hollow cylindrical body having a first end with internal threading, and a second end, an externally threaded cylinder protruding from the second end and, a rim circumscribing the hollow cylindrical body between the first end and the second end.

The present disclosure also comprises a mounting assembly for a nozzle, the nozzle comprising an inlet end, a discharge end and a universal connector adapted to connect to the inlet end of the nozzle, the universal connector comprising a hollow cylindrical body having a first end with internal threading, and a second end, an externally threaded cylinder protruding from the second end and a rim circumscribing the hollow cylindrical body between the first end and the second end, the mounting assembly comprising a track, a connector base comprising an arcuate channel to support the universal connector, the connector module further comprising first and second members that connect to the track along a bottom surface, an adjustable locking assembly comprising a strap lock connected to the first member of the connector base, the strap lock comprising a clamping element, a locking strap comprising a locking pin, the locking strap secured to the strap lock by the clamping element, a pin locking element connected to the second member of the connector base and, a latch pivotally attached to the pin locking element, the latch comprising a channel adapted to receive the locking pin, and a locked position, the locking strap is freely movable when the pivoting latch is in a position other than the locked position and, a flexible mount assembly adapted to support the discharge end of the nozzle, the flex mount module comprising a first mount comprising a first rear surface and a first front surface, a first arm extending upwardly from the first mount, the first arm comprising a first extended portion extending from the first arm and, a first base extending outwardly from the first front surface adapted to connect to a track and, a second mount comprising a second rear surface and a second front surface, a second arm extending upwardly from the second mount, the second arm comprising a second extended portion extending from the second arm and, a second base extending outwardly from the second front surface adapted to connect to the track, wherein the first rear surface is in contact with the second rear surface.

A general object of the present disclosure is to provide a mounting point that will be the same for all makes and models of 1.5" diameter nozzles.

Another object of the present disclosure is to provide an efficient and durable locking mount.

A further object of the present disclosure is to provide a locking strap which can be adjusted.

Yet another object of the present disclosure is to provide a mount that can be adjusted for various nozzle diameters and nozzle lengths.

These and other objects, features, and advantages of the present disclosure will become readily apparent upon a review of the following detailed description of the disclosure, in view of the drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1 is a perspective view of an assembly;

FIG. 2A is a perspective view of the assembly shown in FIG. 1 without a locking module;

FIG. 2B is an exploded perspective view of the assembly shown in FIG. 1 without locking module;

FIG. 3A is a perspective view of a connector as shown in FIG. 1;

FIG. 3B is a top view of the connector shown in FIG. 3A;

FIG. 3C is a cross-sectional view of the connector taken generally along line 3C-3C in FIG. 3B;

FIG. 4A is a bottom perspective view of a storage mount;

FIG. 4B is a top view of the storage mount shown in FIG. 4A;

FIG. 4C is a side view of the storage mount shown in FIG. 4A;

FIG. 4D is a front view of the storage mount shown in FIG. 4A;

FIG. 4E is a top perspective view of the storage mount shown in FIG. 4A;

FIG. 4F is a top perspective view of the storage mount shown in FIG. 4A with connector;

FIG. 5A is a perspective view of a base mount as shown in FIG. 1;

FIG. 5B is a front view of the base mount shown in FIG. 5A;

FIG. 5C is a side view of the base mount shown in FIG. 5A;

FIG. 5D is a top view of the base mount shown in FIG. 5A;

FIG. 6A is a front view of a mount of a flexible mount assembly as shown in FIG. 1;

FIG. 6B is a side view of the mount of flexible mount assembly as shown in FIG. 1;

FIG. 6C is a perspective view of the mount of flexible mount assembly as shown in FIG. 1;

FIG. 6D is a front perspective view of the mount of flexible mount assembly as shown in FIG. 1;

FIG. 6E is a back perspective view of the mount of flexible mount assembly as shown in FIG. 1;

FIG. 7A is a perspective view of a locking assembly as shown in FIG. 1;

FIG. 7B is a side view of the locking assembly shown in FIG. 7A in an unlocked position;

FIG. 7C is a side view of the locking assembly shown in FIG. 7A in a locked position;

FIG. 8A is an exploded perspective view of a secondary embodiment of a locking assembly;

FIG. 8B is an exploded perspective view of the locking assembly shown in FIG. 8A;

FIG. 9A is a perspective view of the locking assembly shown in FIG. 7A securing a large canister;

FIG. 9B is a perspective view of the locking assembly shown in FIG. 7A securing a crate; and,

FIG. 9C is a perspective view of the locking assembly shown in FIG. 7A securing a small canister.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements. It is to be understood that the claims are not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the claims.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly

understood to one of ordinary skill in the art to which this disclosure pertains. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the example embodiments. The assembly of the present disclosure could be driven by hydraulics, electronics, pneumatics, and/or springs.

It should be appreciated that the term “substantially” is synonymous with terms such as “nearly,” “very nearly,” “about,” “approximately,” “around,” “bordering on,” “close to,” “essentially,” “in the neighborhood of,” “in the vicinity of,” etc., and such terms may be used interchangeably as appearing in the specification and claims. It should be appreciated that the term “proximate” is synonymous with terms such as “nearby,” “close,” “adjacent,” “neighboring,” “immediate,” “adjoining,” etc., and such terms may be used interchangeably as appearing in the specification and claims. The term “approximately” is intended to mean values within ten percent of the specified value.

Because of the emergency nature of firefighting, the time required to get a hose “on the fire” is of major importance. Consequently, the speed of releasing a pre-connect from a mounting system is of considerable importance. A grab-and-go system, with the fire fighters’ feet on the ground, is most desirable. Any pre-connect nozzle mounting system has to accommodate environmental conditions. Therefore, the present mounting system is resistant to weather extremes, e.g., from subzero temperatures to extreme heat and UV exposure. Moreover, the present system is easily adjustable because the length, size and weight of 1.5" diameter nozzles can vary greatly.

Frequently, 200 feet of 1.5" diameter hose is pre-connected between a pump discharge and a 1½ inch nozzle. To store the hose, the pump discharge valve must be closed, the 1½ inch nozzle valve control opened and any water in the hose drained out. The hose is then folded into the hose bed. In many cases, the nozzle is stored with the nozzle control valve in the open position. The handler valves connected to the nozzle are often quite large. Any mounting of these nozzles must recognize space required not only for the nozzle itself, but also for the handle. Some also include a pistol grip that can often be large. The present system accommodates the foregoing constraints.

Further, the pre-connected nozzle may be required to mount vertically attached to the side of the truck or it may be mounted horizontally on the front bumper or other area. Even further, the length, weight and discharge end of the nozzle can vary greatly so it is necessary that there be a cradle mount for the discharge end that can easily be adjusted to provide a secure customized mount for the nozzle. The result is a locking mount for the base swivel end of the nozzle and a friction clamp type mount for the discharge end. A track system is used to easily adjust the length between the two mounts.

Mounting any equipment on a mobile vehicle must recognize the various gravitational forces generated when the truck runs over bumps or holes in the road. To counter-act these forces, the present disclosure supports both the inlet end and the discharge end of the nozzle. The support on the discharge end is easily adjusted to not only a wide range of diameters but also to variances in the distance between the inlet end and discharge end of the nozzles. The current disclosure allows for easy movement and be securely locked into position once a dimension is finalized.

Referring now to the Figures, FIG. 1 shows assembly 100 as an embodiment of the present disclosure. Assembly 100 broadly comprises nozzle 10, universal connector 20, con-

connector base 30, flexible mount assembly 40, locking assembly 50, and track 80. Universal connector 20 attaches to inlet end 14 of nozzle 10. Universal connector 20 is supported by connector base 30 and securely locks into place by locking assembly 50. Further, discharge end 12 of nozzle 10 is supported by flexible mount assembly 40. Flexible mount assembly comprises mounts 41, which are identical to one another, and further comprise arms 46. Arms 46 at least partially circumscribe nozzle 10 and are flexible to accommodate many nozzle diameters of nozzle 10. Mount 41 comprises aperture 41b which allows screws 43 to secure mount 41 to track 80. Since flexible mount assembly 40 is adjustable to accommodate multiple nozzle diameters, screws 43 remove to adjust mounts 41 on track 80 and secure mounts 41 in a new position on track 80. Assembly 100 adjusts as to the length of nozzle 10 due to flexible mount 40 and connector base 30 being attached to track 80, i.e., connector base 30 and flexible mount assembly 40 may move within track 80. Connector base 30 secures to track 80 along surface 30a by screw 32 and adjusts on track 80 to accommodate different nozzle lengths. Locking assembly 50 comprises base 51, base 52, locking strap 54, latch 55, locking pin 56, and strap lock 58. Base 51 and base 52 secure to connector base 30 by screws 31. Strap lock 58 is arranged on base 51 and fixes the length of locking strap 54, which can be adjusted. Locking strap 54 secures universal connector 20 along surface 21 to connector base 30 and is secured in place by latch 55. Latch 55 is rotatably secured to base 52 and is arranged to engage with locking pin 56 of locking strap 54. Track 80 comprises channels 81 which run the length of track 80 and extensions 84 on either side to allow track 80 to be mounted to any surface, such as the body of a fire truck.

FIGS. 2A and 2B are a perspective view and an exploded perspective view, respectively, of assembly 100 of the present disclosure without locking module 50. It is shown in the figures that connector base 30 comprises channel 35 which rim 23 of universal connector 20 engages when nozzle 10 is secured within assembly 100. Universal connector 20 comprises external threads 24 on surface 28 which allow universal connector 20 to secure to inlet end 14 of nozzle 10. Additionally, universal connector 20 comprises internal threads 22 within aperture 25. Threads 22 allow a fire hose to be connected to universal connector 20 and aperture 25 allows water or fluid to flow through universal connector 20 into inlet end 14 of nozzle 10. FIG. 2B shows flexible mount assembly 40 is made of two identical mounts 41 facing opposite to one another.

FIGS. 3A, 3B, and 3C are a perspective view, a top view, and a cross-sectional view, respectively, of nozzle connector 20 taken generally along line 3C-3C in FIG. 3B. Nozzle connector 20 allows for a common mounting area for all 1½ inch nozzles. In a preferred embodiment, rim 23 has a coarse knurled texture which helps prevent universal connector 20 from becoming dislodged from channel 35 of base mount 30 (shown in FIG. 2B). Rim 23 can engage connector base 30 via channel 35 (shown in FIG. 2A) for a pre-connected universal connector with nozzle 10, or engage lip 62 and tab 66 (shown in FIG. 4F) on storage mount 60. Rim 23 extends radially outward in a greater amount than both surface 21 and surface 28 in order to secure with channel 35 (shown in FIG. 2A). In order to connect to any nozzle 10 or fire hose (not shown), internal threads 22 are arranged within aperture 25 and external threads 24 are arranged on surface 28 of universal connector 20. It should be appreciated, however, that the use of different thread arrangements and securement means is possible and considered to be within the scope of

the present disclosure. For example, internal threads 22 could be arranged on surface 21 of universal connector 20 in order to accommodate a new type of fire house connection.

The 1.5" diameter swivel on every nozzle is substantially similar; therefore the present mounting system is related to this connection. A 1.5" diameter internal threading 22 and a 1.5" diameter external threading 24 of connector 20 are installed between and join the discharge end of the 1.5" diameter hose and the 1.5" diameter swivel inlet of a nozzle thereby providing a common dimensional structure for mounting all nozzles. Universal connector 20 may be anodized with NFPA recognized colors thereby serving to identify the 1.5" diameter discharge valve at a pump panel with a particular pre-connected line.

Further, universal connector 20 enables the nozzle to be mounted on a firefighter's hip with a hip holster. A hip mounted holster provides efficient movement in and out in order to relieve strain on a fire fighter's arms while pulling or using the discharge from the nozzle on the fire. Nozzle reaction forces on a 1.5" diameter nozzle discharging 150 GMP at 100 PSI are intense, often requiring two men to handle the hose and nozzle. By transferring reaction forces from arms to the hip greatly reduces fatigue. Likewise, dragging a 1.5" diameter line filled with water is extremely tiresome for the firefighter.

FIGS. 4A, 4B, 4C, 4D, and 4E are a bottom perspective view, top view, side view, front view, and top perspective view of storage mount 60, respectively. Storage mount 60 has plank 64 comprising tab 66. Tab 66 abuts connector 20 to secure connector 20 sturdily in place by prohibiting radial movement. Further, plank 64 is flexible for easy attachment and detachment of connector 20 simply by pushing on the tip of plank 64, which displaces tab 66 downward thereby freeing radial movement of connector 20. FIG. 4F shows universal connector 20 secured within storage mount 60. Lip 62 extends inwardly to interact with rim 23 and surface 28 of universal connector 20 in order to prohibit axial movement. Storage mount 60 comprises apertures 65 which allow storage mount 60 to be mounted to track 80 (shown in FIG. 2B) or on a surface such as the body of a fire truck (not shown).

FIGS. 5A, 5B, 5C, and 5D are a perspective view, front view, side view, and top view, respectively, of connector base 30. In a preferred embodiment, channel 35 is arcuate in shape and aligns with rim 23 of universal connector 20. It should be appreciated, however, that the use of different shapes of channel 35 is possible and considered to be within the scope of the present disclosure. Universal connector 20 rests on member 36a and member 36b while rim 23 of universal connector 20 sits within channel 35 for added stability. Connector base 30 has surface 30a that interacts with track 80 (shown in FIG. 1), and mounting channels 33a and 33b to secure base 51 and base 52 of locking assembly 50.

FIGS. 6A, 6B, 6C, 6D, and 6E are a front view, side view, perspective view, front perspective view, and back perspective view, respectively, of mount 41 of flexible mount assembly 40. As shown in the figures, mount 41 comprises aperture 42, surface 43a, surface 43b, arm 46, and base 49. Aperture 42 allows for a screw (not shown) or some securement means to secure two identical mounts 41 facing opposite one another on track 80 (shown in FIG. 1). Surface 41a of base 49 connects mount 41 to track 80 so it can be adjusted to the desired distance along the track. The combination of two arms 46 engaging along surface 43b forms a full cradle along surfaces 47. Arm 46 is designed to be flexible to allow ease of disengagement of nozzle 10 from

flexible mount assembly **40** (shown in FIG. 1). Nozzle **10** can be snapped into place simply by pushing nozzle **10** through the space between the tips of each arm **46**. Further, the slotted base of mount **41** and the mating surfaces of arms **46** permit the gap between arms **46** to be adjusted. This adjustability enables arms **46** to accommodate larger or smaller diameter articles to be supported. In a preferred embodiment, arm **46** is integral to mount **41**. It should be appreciated, however, that the use of different shapes and materials for arm **46** is possible and considered to be within the scope of the present disclosure. For example, arm **46** could be made from a plastic which deforms with less force when compared to the material which mount **41** is manufactured from to make disengagement easier. Additionally, arm **46** could be designed with a hinge or slide means to keep nozzle **10** secured within assembly **100**. Arm **46** has extended portion **48**, which creates a thin portion of arm **46** and a thick portion of arm **46**. This allows the thickness of flexible mount assembly **40** as a whole to be consistent when mounts **41** are situated facing oppositely along track **80**. In this way, the thin portion of the curved arms creates a uniform thickness for the portion supporting nozzle **10** because the thin portions of each arm **46** contact the thin portion of the other arm **46**.

FIGS. 7A, 7B, and 7C are a perspective view, a side view of locking assembly **50** in an unlocked position, and a side view of locking assembly **50** in a locked position, respectively. Locking assembly **50** comprises mount **51**, mount **52**, locking strap **54**, latch **55**, locking pin **56**, and strap lock **58**. Locking strap **54** traverses a space from mount **51** to mount **52**. One end of locking strap **54** is clamped to strap lock **58** with the other end having locking pin **56** engaging latch **55**. Mount **52** has latch **55** which can either release locking strap **54** or secure it in place. Locking pin **56** is threaded through an aperture in locking strap **54** and secured within channel **55a** of latch **55** when latch **55** is in an upright position. FIG. 7B shows latch **55** in the upright position. When locking strap **54** is secured within channel **55a** of latch **55** and fixed to the desired length by using strap lock **58**, pushing latch **55** downwards about its pivotable connection on mount **52** locks strap **54** in place. In a preferred embodiment, strap **54** comprises ridges on the top surface to ensure stability. It should be appreciated, however, that the use of different stability means for locking strap **54** are possible and considered to be within the scope of the present disclosure. For example, locking strap **54** could comprise apertures symmetrically arranged along the length of locking strap **54**. The apertures could then be engaged by a screw arranged within strap lock **58**. For further stability, i.e., for cylinders, supports **59** are optionally provided and secure to track **80** (shown in FIG. 9A).

FIG. 8A and FIG. 8B are exploded perspective views of a secondary embodiment of locking assembly **50** without mount **51** and mount **52**. Pin locking element **70** engages with locking pin **56** of locking strap **54** via channels. Strap lock **58** comprises clamping element **58a** and base **58b**. Clamping element **58a** and base **58** are secured to one another via screws **61** and fix the length of locking strap **54**. Locking strap **54** can be smooth and elastic, smooth and rigid, ridged and elastic, or ridged and rigid. Locking assembly **50** can be attached to the adjustable mounting assembly **100** with spacing between strap lock **58** and pin locking element **70** dictated by connector base **30** (shown in FIG. 1). Alternatively, the spacing between strap lock **58** and pin locking element **70** can be maintained by arranging insert **57** within channels **81** of track **80** as shown in FIGS. 8A and 8B. Strap lock **58** is secured in channel **81** of track

80 via screw **61** and bushing **63**. Additionally, and pin locking element **70** is secured in channels **81** of track **80** via screw **61** and bushing **63**. If it is desired that strap lock **58** and pin locking element **70** be positioned above track **80**, guide **57a** can be secured to track **80** via screws **61** and bushings **63**.

FIGS. 9A, 9B, and 9C are perspective views of locking assembly **50** demonstrating its capability of locking various objects to track **80**. As shown in the figures, locking assembly **50** can lock large canister **90**, crate **91**, and small canister **92** to track **80** for transportation or storage. It is important to note that supports **59** are only required for large canister **90** and small canister **92** due to the arcuate outer surface of each canister. Similar to nozzle **10** (shown in FIG. 1), locking assembly can be secured to track **80** at any position along its length, such that multiple locking assemblies **50** can be secured within the same channels **81** of track **80**.

It will be appreciated that various aspects of the disclosure above and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

LIST OF REFERENCE NUMBERS

10	Nozzle
12	Discharge end
14	Inlet end
20	Universal connector
21	Surface
22	Internal threads
23	Rim
24	External threads
25	Aperture
28	Surface
30	Connector base
30a	Surface
32	Screw
33a	Channel
33b	Channel
35	Channel
36a	Member
36b	Member
40	Flexible mount assembly
41	Mount
41a	Surface
41b	Aperture
42	Aperture
43	Screws
43a	Front surface
43b	Rear surface
46	Arm
47	Surface
48	Extended portion
49	Base
50	Locking assembly
51	Mount
52	Mount
54	Locking strap
55	Latch
55a	Channel
56	Locking pin
57	Insert
57a	Guide

- 58 Strap lock
- 58a Clamping element
- 58b Base
- 59 Support
- 60 Storage mount
- 61 Screws
- 62 Lip
- 63 Bushing
- 64 Plank
- 65 Aperture
- 66 Tab
- 70 Locking element
- 80 Track
- 81 Channels
- 84 Extension
- 90 Large canister
- 91 Crate
- 92 Small canister
- 100 Assembly

What is claimed is:

1. An adjustable locking assembly, comprising:
 a track;
 a first mount and a second mount, the second mount being spaced apart from the first mount, the first and second mounts being non-pivotable with respect to each other, wherein the first and second mounts are adjustably secured to the track;
 a connector base arranged proximate the first and second mounts, the connector base including a first channel and a second channel, the first mount secured in the first channel and the second mount secured in the second channel;
 a strap lock connected to the first mount and including a clamping element;
 a locking strap including a first end connected to the strap lock and a second end fixedly secured to a locking pin; and,
 a pin locking element connected to the second mount and including a pivoting latch, the pivoting latch including a channel arranged to receive the locking pin;
 wherein:
 in a locked position, the locking pin is secured in the channel and the pivoting latch is pivoted away from the strap lock; and,
 in an unlocked position, the locking strap is freely movable.
2. The adjustable locking assembly as recited in claim 1, further comprising a pair of supports between the strap lock and the pin locking element.
3. The adjustable locking assembly as recited in claim 1, wherein the locking strap further comprises one or more ridges.
4. The adjustable locking assembly as recited in claim 3, wherein the one or more ridges on the locking strap engage with the strap lock.
5. The adjustable locking assembly as recited in claim 1, wherein the length of the locking strap is adjustable.
6. The adjustable locking assembly as recited in claim 1, wherein the locking strap engages with a universal connector.
7. The adjustable locking assembly as recited in claim 1, wherein the connector base is connected to the track along a bottom surface of the connector base.
8. The adjustable locking assembly as recited in claim 1, wherein the connector base comprises an arcuate channel arranged to support a universal connector.

9. The adjustable locking assembly as recited in claim 1, further comprising a flexible mount assembly connected to the track.
10. The adjustable locking assembly as recited in claim 1, wherein the clamping element secures the locking strap via one or more screws.
11. A mounting assembly for a nozzle, the nozzle comprising an inlet end, a discharge end and a universal connector adapted to connect to the inlet end of the nozzle, the universal connector comprising a hollow cylindrical body having a first end with internal threading, and a second end, an externally threaded cylinder protruding from the second end and a rim circumscribing the hollow cylindrical body between the first end and the second end, the mounting assembly comprising:
 a track;
 a connector base connected to the track, the connector base including a channel arranged to support the universal connector;
 an adjustable locking assembly, including:
 a strap lock including a clamping element;
 a locking strap including a first end connected to the strap lock and a second end fixedly secured to a locking pin, the first end operatively arranged to be slidable with respect to the strap lock and fixedly secured thereto by the clamping element; and,
 a pin locking element including a pivoting latch, the pivoting latch including a channel arranged to receive the locking pin, wherein the locking pin is operatively arranged to be completely disengageable from the pivoting latch;
 wherein:
 in a locked position, the locking pin is secured in the channel and the pivoting latch is pivoted away from the strap lock; and,
 in an unlocked position, the locking strap is freely movable; and,
 a flexible mount assembly connected to the track and arranged to support the discharge end of the nozzle, wherein the flexible mount assembly and the connector base are displaceable on the track independently of each other.
12. The mounting assembly as recited in claim 11, wherein the locking strap is arranged to secure the universal connector to the connector base.
13. The mounting assembly as recited in claim 11, wherein the flexible mount assembly comprises:
 a first mount, including:
 a first body having a first rear surface and a first front surface;
 a first arm extending upwardly from the first body, wherein the first arm is apertureless; and,
 a first base extending substantially perpendicular from the first front surface and adapted to connect to the track, wherein the first base comprises at least one first aperture; and,
 a second mount comprising:
 a second body including a second rear surface and a second front surface;
 a second arm extending upwardly from the second body, wherein the second arm is apertureless and not directly connected to the first arm; and,
 a second base extending substantially perpendicular from the second front surface and adapted to connect to the track, wherein the second base comprises at least one second aperture, and the first rear surface is in contact with the second rear surface;

13

14

wherein the first mount and the second mount are displaceable in a first direction and a second direction, opposite the first direction, to adjust a distance between the first and second arms.

14. The mounting assembly as recited in claim **13**,
5 wherein the first arm and the second arm form a cradle to support a discharge end of a nozzle.

15. The mounting assembly as recited in claim **13**,
10 wherein the first arm and the second arm are flexible members.

* * * * *