



US010837420B2

(12) **United States Patent**
Suddaby

(10) **Patent No.:** **US 10,837,420 B2**
(45) **Date of Patent:** **Nov. 17, 2020**

(54) **WAVE ENERGY CAPTURE DEVICE AND ENERGY STORAGE SYSTEM UTILIZING A VARIABLE MASS, VARIABLE RADIUS CONCENTRIC RING FLYWHEEL**

1,930,958 A	10/1933	Parsons
3,335,667 A	8/1967	Murphy
3,353,787 A	11/1967	Semo
3,362,336 A	1/1968	Kafka
3,683,216 A	8/1972	Post
3,961,863 A	6/1976	Hooper, III
4,145,882 A	3/1979	Thorsheim
4,170,738 A	10/1979	Smith
4,223,240 A	9/1980	Theyse
4,228,360 A	10/1980	Navarro
4,268,226 A	5/1981	Morris

(Continued)

(71) Applicant: **Loubert S. Suddaby**, Orchard Park, NY (US)

(72) Inventor: **Loubert S. Suddaby**, Orchard Park, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 71 days.

FOREIGN PATENT DOCUMENTS

AU	2015202311	5/2019
CA	2729927	1/2010

(Continued)

(21) Appl. No.: **16/176,094**

(22) Filed: **Oct. 31, 2018**

(65) **Prior Publication Data**

US 2020/0132039 A1 Apr. 30, 2020

(51) **Int. Cl.**
F03B 13/18 (2006.01)
F15B 15/10 (2006.01)
F03G 3/08 (2006.01)

(52) **U.S. Cl.**
 CPC **F03B 13/181** (2013.01); **F03G 3/08** (2013.01); **F15B 15/106** (2013.01)

(58) **Field of Classification Search**
 CPC F03B 13/26; F03B 13/16; F05B 2240/93; F05B 2260/4031; F05B 2220/706
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS


1,008,682 A	11/1911	Wall
1,455,718 A	5/1923	Delong

Primary Examiner — Shafiq Mian
 (74) Attorney, Agent, or Firm — Simpson & Simpson, PLLC

(57) **ABSTRACT**

An assembly for generating energy from waves, comprising a concentric ring flywheel operatively arranged to generate electrical current, the concentric ring flywheel comprising a first shaft including an input end and an output end, a plurality of rings, the plurality of rings including at least a first ring, including a first radially inward facing surface arranged to connect with the output end of the first shaft, and a first radially outward facing surface, a second ring arranged concentrically around the first ring, the second ring including a second radially inward facing surface and a second radially outward facing surface, one or more first clutch connectors arranged in a first space radially arranged between the first and second rings to non-rotatably connect the second ring and the first ring, and a wave energy capture device operatively arranged to rotate the first shaft.

31 Claims, 13 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4A







Fig. 4B






Fig. 6A




Fig. 6B




Fig. 7




Fig. 9A




Fig. 9B




Fig. 9C




Fig. 10C

1

**WAVE ENERGY CAPTURE DEVICE AND
WAVE ENERGY STORAGE SYSTEM UTILIZING A
VARIABLE MASS, VARIABLE RADIUS
CONCENTRIC RING FLYWHEEL**

FIELD

The present disclosure relates to wave energy capture devices, and more particularly, to wave energy capture devices that function in concert with a variable mass, variable radius concentric ring flywheel that permits simultaneous energy storage and energy conversion capabilities.

BACKGROUND

A cresting wave is an almost pure embodiment of captured kinetic and potential energy sourced by the sun. Mankind has long yearned to utilize this energy for purposes beyond the capricious exhilaration provided by a surfboard. As a consequence of this quest, numerous devices have been proposed to harness this energy, but virtually none have achieved much beyond a modicum of subsidized and propagandized commercial success.

The biggest challenge in energy capture resides in the unpredictability of the oscillatory nature of ocean waves, in amplitude, direction, and periodicity. Additional challenges reside in converting the massive monotony of wave energy into the hundreds of revolutions per minute required to produce useful mechanical or electrical energy. Finally, to achieve a seamless and constant supply of such converted energy, a storage mechanism is required for when the inevitable doldrums arrive. The summation of these challenges, therefore, is to provide for a device or devices that can capture the voluminous but slow kinetic energy of ponderous waves and convert them to high speed unidirectional continuous rotation of a shaft that can power a generator.

Thus, there is a long felt need for a wave energy capture device which is simple to manufacture and permits simultaneous energy storage and energy conversion capabilities.

SUMMARY

According to aspects illustrated herein, there is provided a concentric ring flywheel arranged to interact with at least one stator for generating electrical current, the concentric ring flywheel comprising a shaft, a plurality of rings, the plurality of rings including at least a first ring, including a first radially inward facing surface arranged to connect with the shaft, and a first radially outward facing surface, a second ring arranged concentrically around the first ring, the second ring including a second radially inward facing surface, and a second radially outward facing surface, wherein a first space is arranged radially between the first radially outward facing surface and the second radially inward facing surface, and one or more first clutch connectors arranged in the first space to non-rotatably connect the second ring and the first ring.

According to aspects illustrated herein, there is provided an assembly for generating energy from waves, comprising a concentric ring flywheel operatively arranged to interact with at least one stator for generating electrical current, the concentric ring flywheel comprising a first shaft including an input end and an output end, a plurality of rings, the plurality of rings including at least a first ring, including a first radially inward facing surface arranged to connect with the output end of the first shaft, and a first radially outward

2

facing surface, a second ring arranged concentrically around the first ring, the second ring including a second radially inward facing surface and a second radially outward facing surface, wherein a first space is arranged radially between the first radially outward facing surface and the second radially inward facing surface, one or more first clutch connectors arranged in the first space to non-rotatably connect the second ring and the first ring, and a wave energy capture device operatively arranged to rotate the first shaft.

It is an object of the present disclosure to provide a simple shore based mechanism for wave energy capture. Shore based capture is preferred for ease of maintenance of the device and because captured energy must ultimately be transferred to land to be stored, dispersed, and utilized. It is also an object of the present disclosure to provide a simple and efficient mechanism to store energy captured from waves to allow a consistent and seamless supply of power to the existing power grid.

To achieve these ends, wave energy capture is performed using one of four different mechanisms, though the energy storage mechanism described herein is compatible with any wave energy harvesting device, or indeed, any device producing energy.

In some embodiments, the wave energy capture device utilizes a float pivotally attached to a lever arm. The lever arm, in turn, is unique insofar as it varies in stiffness at opposite ends, with the changeable characteristic of the shaft occurring roughly at a fulcrum positioned along the shaft. The distal end of the lever arm is flexible and pivotally bound to said float. By being flexible, variations in wave energy can be moderated by converting the mechanical energy into elastomeric potential energy stored in the shaft. Further adaption to the wave amplitude can be achieved by a moveable fulcrum which translates along the shaft in a forward or backward direction depending on the need to control energy transfer. The position of the shaft proximal to the mobile fulcrum is stiffer and its up and down excursions are limited by an oscillation restrictor to prevent damage to the energy capture mechanism. The energy capture mechanism employs, in the simplest iteration, a free wheel mechanism or a spiral plunger mechanism to convert oscillatory motion to rotary motion. These mechanisms, for example, may be similar to those used in the pedal mechanism of a bicycle or, in the case of the spiral plunger mechanism, a toy pump top. However, it is understood that a variety of mechanical devices that convert oscillatory motion to rotator motion could be employed.

Once energy conversion to rotary form has been achieved, by whatever mechanism, the energy so produced is immediately stored in a concentric ring variable mass, variable radius flywheel such that the unpredictable wave energy can be continuously and controllably accessed. A flywheel is the preferred embodiment because they can achieve energy storage efficiently that exceeds 90% whereas battery storage is around 30-40%. Flywheels also cause less damage to the environments, function over a wider temperature range than a battery and require low maintenance. James Watt's steam engine flywheels continue to work after 200 years. The flywheel employed in this energy storage is unique and will be described in detail.

In some embodiments, the wave energy capture device involves a shore based wave chamber containing a heavy cylinder pivotally attached at each end to a spring or similar elastomeric device. The floor of the wave chamber is sinusoidal or curved such that when the cylinder is pushed away from the intake opening by a wave, the cylinder rolls away from its resting place and then down along a curved surface

and then up the distal wall until all kinetic energy is expanded, whereupon the cylinder falls back and is pulled by the springs to its resting place until displaced by the next wave.

As the cylinder is displaced by the wave it compresses an elastomeric compartment or hose or series thereof positioned along the floor of the wave chamber. The elastomeric chambers or hoses are, in turn, connected to a non-elastomeric hose or pipe containing one way valves. As the compressing cylinder rolls along the sinusoidally shaped floor it compresses elastomeric hoses or compartments along the floor of the wave chamber. The water contained within the compressible hose or compartments is displaced out of the chamber and up a pipe or conduit toward an elevated container or cistern. One way valves within the conduit prevent return of expressed water into the chamber such that each sequential wave displacement forces water into the cistern thereby converting kinetic energy into potential energy. The water contained in the cistern is then released to either directly power a turbine to generate electrical energy or transferred to a flywheel for storage prior to conversion to electrical energy.

The amount of energy captured can be varied dependent upon the height and periodicity of the waves and controlled by a number of factors, for example, size and weight of the cylinders, caliber of the elastomeric hose and conduits or compressible compartments, distance between one way valves (volume of water contained therein), height of the cistern, and the mass and speed of the flywheel (if used).

Many of the components of the peristaltic wave pumps can be made of cement or plastics that resist corrosion and hence function longer in a marine environment.

In some embodiments, the wave energy capture device employs a linear actuator-type absorber, which functions as a sinusoidal pump. This iteration involves a series of mechanical pumps connected in series like beads on a string. The rising force of a wave or swell causes angular flexion between segments of the linear actuator, which is positioned perpendicular to the direction off the waves.

Flexion up or down tautens a cable connected to a piston valve contained within a segment. The cable pulls the piston linearly along a segment and displaces water contained therein into a flexible fabric hose strung in parallel along the linear actuator via a one-way valve. When the flexed segment returns to a neutral position, a spring or elastomeric member pulls the piston back into position and water refills the chamber through a separate one-way valve. The tautening cables are positioned via pulleys such that a flexion force triggered by the rise and fall of a wave will displace the piston pump no matter which direction the wave displaces adjacent segments. In this fashion, water can be pumped with either the rise or the fall of a wave. Displaced water, in turn, is pushed along the linear actuator via the fabric hose and into a cistern where it is stored as potential energy to be utilized later.

In some embodiments, the wave energy capture device employs a peristaltic pump application that is not surface-based. The wave energy capture device captures wave energy on the ocean floor so that it can be employed or deployed in areas with high surface recreational activity. This iteration employs a fan shaped wave capture device oriented in parallel to an incoming wave. As waves approach a shore, the base of the wave is actually in contact with the ocean floor and accounts for the "to and fro" motion observed in sea weed and kelp that grow up from the bottom. Any scuba diver will attest to the significant force of these invisible waves that manifest their surface extensions as

varying undulations or white caps. The force not only moves giant kelp plants forward and then backward, but can also displace large objects in a similar fashion.

To capture this deep wave energy, a fan shaped actuator is attached to a stem which in turn is pivotally attached to a floor based anchor. Said anchor, in turn, contains a fabric hose which can be compresses in a peristaltic fashion when the wave capture device moves to and fro. The fabric hose contains one-way valves that allow displaced water to be pumped to a land based cistern, which in turn stores the water for later release to power a turbine. The sea floor-based peristaltic pumps can be placed in series along a single compressible hose or vessel, or in parallel such that multiple pumps can operate unseen beneath the waves at any one time. In this fashion, numerous peristaltic pumps can operate to fill one or more cisterns thereby exploiting the kinetic energy of waves and tides in a continuous fashion.

The present disclosure also includes a unique flywheel configuration that serves to store energy but also can be utilized to generate electrical energy by virtue of the fact that the energy is stored as rotational kinetic energy and that rotational kinetic energy is easily converted to electrical energy by placing copper coiling around magnetic rotors located in the perimeter of the flywheel, or one or more of its' concentric ring subparts.

The present disclosure utilizes a concentric ring flywheel design with each ring planar to the next ring but rotating on separate mechanical or magnetic bearings such that each ring is capable of being spun or rotated at a different speed than the others. A shaft would drive the innermost ring like a conventional flywheel, and, by virtue of its' smaller size, the inner ring would be easier to power up by virtue of its' lesser mass and radius.

On the outer surface of each ring are contact points that are reversibly contacted with the inner circumference of the adjacent ring. These contact points are actuated like a centrifugal clutch in the purely mechanical iteration, or electronically via wireless communication, for example, Bluetooth® wireless communication, in the computerized electronic version.

In the mechanical version of the concentric ring flywheel, once the inner ring reaches a predetermined speed in revolutions per minute (RPM), the outer centrifugal clutch engages the adjacent outer ring and starts it spinning. Once the adjacent ring reaches a predetermined speed its outer centrifugal clutch engages the next ring such that progressively greater amounts of energy can be stored by transferring energy to adjacent rings. If the shaft RPM drops, the centrifugal clutch in its' outer perimeter disengages so that the adjacent ring continues to spin unencumbered by the lapse in energy input. In energy rich times, progressively more energy is shifted to the outer more massive rings capable of greater energy storage. It is anticipated that electrical energy will be more consistently generated from outer rings of the concentric flywheel, which are more likely to retain a more constant degree of angular momentum, particularly in the mechanical centrifugal clutch version.

In the electronic version of the concentric ring flywheel, connection between concentric rings is controlled by a computer that calculates the optimal RPM to transfer energy between rings and activates the electronic clutch mechanism between rings via a wireless type of connection (i.e., wireless communication). In this fashion, both mass and radius can be varied almost instantaneously in an effort to keep one of the rings spinning at a constant rate to ensure that the oscillation energy in a wave can be converted to a consistent stable and accessible energy source. For example, middle

rings could be kept at an optimal 1,800 RPM by transferring stored energy from an outer ring inward or from an inner ring outward.

In some embodiments, the concentric rings are arranged on magnetic bearings, in a vacuum, whereupon energy efficiency can exceed 95%.

The shaft connection with the innermost ring would employ a free wheel or other clutch mechanism with variable gearing that promotes the highest RPM to energy input achievable. In some embodiments, the gear selection would be computerized and electronically selected as well, in a manner similar to an automatic transmission in a vehicle.

In times of low wave energy input, the shaft may disconnect from the flywheel to limit frictional energy loss but in times of high wave energy input the energy would be progressively transferred to the larger, heavier output rings having greater angular momentum and hence greater energy storage. By locating rotors adjacent to the concentric rings, the concentric flywheel assembly can serve simultaneously for energy storage and for conversion of kinetic energy into electrical energy.

To achieve even greater energy density and control, each of the concentric rings, while planar on the top, will have a non-planar or parabolic undersurface. The space between the upper and lower surfaces in turn, would be hollow and contain fluid such as water in the simplest iteration, or mercury if high mass is deemed desirable. Additionally, the lower surface will have ridges or concentric compartments with centrifugally or electronically controlled gates to allow control of the fluid as centrifugal force pushes it outward and up the incline toward adjacent compartments. Greater angular velocity would concentrate fluid toward the outer edge of a concentric ring and lower angular velocity would allow gravity to draw the fluid back inward and restore mass concentration centrally. Ridges would control the transfer of fluid in the simplest iteration and concentric compartments would control fluid transfer via electronic or centrifugally controlled gates in the more complex version.

These and other objects, features, and advantages of the present disclosure will become readily apparent upon a review of the following detailed description of the disclosure, in view of the drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1 is an elevational view of a wave energy capture device;

FIG. 2 is a perspective view of a wave energy capture device;

FIG. 3 is a perspective view of a wave energy capture device;

FIG. 4A is a cross-sectional view of a wave energy capture device in a relaxed state;

FIG. 4B is a cross-sectional view of the wave energy capture device shown in FIG. 4A, in a flexed state;

FIG. 5A is an elevational view of a wave energy capture device in a first position;

FIG. 5B is an elevational view of the wave energy capture device shown in FIG. 5A, in a second position;

FIG. 5C is an elevational view of the wave energy capture device shown in FIG. 5A, in a third position;

FIG. 6A is an elevational view of a wave energy capture device;

FIG. 6B is a partial cross-sectional view of the wave energy capture device shown in FIG. 6A;

FIG. 7 is a perspective view of a flywheel;

FIG. 8 is an elevational view of a flywheel;

FIG. 9A is a cross-sectional view of the flywheel taken generally along line 9-9 in FIG. 8B, in a first state;

FIG. 9B is a cross-sectional view of the flywheel taken generally along line 9-9 in FIG. 8, in a second state;

FIG. 9C is a cross-sectional view of the flywheel taken generally along line 9-9 in FIG. 8, in a third state;

FIG. 10A is a cross-sectional view of the flywheel taken generally along line 10-10 in FIG. 8, in a first state;

FIG. 10B is a cross-sectional view of the flywheel taken generally along line 10-10 in FIG. 8, in a second state; and,

FIG. 10C is a cross-sectional view of the flywheel taken generally along line 10-10 in FIG. 8, in a third state.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements. It is to be understood that the claims are not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the claims.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure pertains. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the example embodiments. The assembly of the present disclosure could be driven by hydraulics, electronics, pneumatics, and/or springs.

It should be appreciated that the term “substantially” is synonymous with terms such as “nearly,” “very nearly,” “about,” “approximately,” “around,” “bordering on,” “close to,” “essentially,” “in the neighborhood of,” “in the vicinity of,” etc., and such terms may be used interchangeably as appearing in the specification and claims. It should be appreciated that the term “proximate” is synonymous with terms such as “nearby,” “close,” “adjacent,” “neighboring,” “immediate,” “adjoining,” etc., and such terms may be used interchangeably as appearing in the specification and claims. The term “approximately” is intended to mean values within ten percent of the specified value.

By “non-rotatably connected” elements, we mean that: the elements are connected so that whenever one of the elements rotate, all the elements rotate; and relative rotation between the elements is not possible. Radial and/or axial movement of non-rotatably connected elements with respect to each other is possible, but not required. By “rotatably connected” elements, we mean that the elements are rotatable with respect to each other.

Referring now to the figures, FIG. 1 is an elevational view of wave energy capture device 10. Wave energy capture device 10 generally comprises wave chamber 20, cylinder 40, hose 50, cistern 70, and flywheel 100.

Chamber 20 comprises opening 22, floor 24, section 28, and opening 30. Floor 24 is curvilinear (e.g., sinusoidally shaped) and includes end 24A and end 24B. End 24A is arranged in the front of wave chamber 20 proximate opening 22, whereas end 24B is arranged in the rear of wave chamber

20 proximate opening 30. In some embodiments, floor 24 is linear. In some embodiments, floor 24 is linear and sloped downward from end 24A to end 24B. Section 28 is generally an overhang arranged above floor 24. Chamber 20 is positioned at least partially in water 2 such that waves flow into and out of opening 22. For example, chamber 20 may be arranged on a shore adjacent a body of water such that waves flow in and out thereof. Chamber 20 may further comprise wave gate 26 which is rotatably connected to chamber 20 proximate end 24A to regulate the magnitude of the waves entering opening 22. Wave gate 26 may be adjusted manually or be controlled remotely via wireless communication. For example, wave gate 26 may be connected to a motor having a wireless communication receiver. A wireless communication transmitter may be used to send a signal to the wireless communication receiver to activate the motor and position wave gate 26 accordingly. If the magnitude of the waves of water 2 are, for example, very large, wave gate 26 may be raised in order to reduce the wave magnitude entering opening 22. If the magnitude of the waves of water 2 are, for example, moderate to small, wave gate 26 may be lowered to allow the full magnitude of the waves to enter opening 22. In some embodiments, wave chamber 20 is connected to rail 32. Rail 32 allows chamber 20 to be repositioned for tidal adjustments, via, for example, a sliding engagement therebetween. In low tide environments, wave chamber 20 may be adjusted in direction B relative to rail 32. In high tide environments, wave chamber 20 may be adjusted in direction A relative to rail 32.

Hose 50 is arranged along floor 24. Hose 50 is at least partially elastomeric. By elastomeric, it is meant that hose 50 is compressible and will return to its original shape after being compressed. In some embodiments, hose 50 is completely elastomeric. In some embodiments, hose 50 is partially elastomeric and partially rigid, for example, portion 50A may be rigid. Hose 50 comprises intake valve 52. Water 2 enters hose 50 via intake valve 52 and fills hose 50. Hose 50 further comprises one or more one-way valves. Intake valve 52 may be, for example, a one-way valve. In some embodiments, negative pressure within hose 50, created by elastomeric hose 50 returning to its original shape after being compressed, causes water 2 to be sucked into intake valve 52. In some embodiments, intake valve 52 and portion 50A are completely submerged in water 2, thereby allowing for portion 50A to be constantly filled with water. Hose 50 extends from intake valve 52, which is positioned at opening 22, to opening 30 where it is connected to conduit 56. In the embodiment shown, hose 50 comprises one one-way valve 54. It should be appreciated that hose 50 may comprise any number of valves suitable for expressing water therein to conduit 56, as will be discussed in greater detail below. In some embodiments, wave energy capture device 10 comprises a plurality of hoses arranged along floor 24.

Cylinder or object or float 40 is positioned in wave chamber 20 and comprises radially outward facing surface 42. Cylinder 40 is connected to chamber 20, specifically overhang section 28, via one or more springs. In the embodiment shown, spring 46A connects cylinder 40 to section 28 via point 44A, and spring 46B (not shown) connects cylinder 40 to section 28 via point 44B (not shown). In some embodiments, cylinder 40 is at least partially hollow and is arranged to roll and/or slide along floor 24 and on top of hose 50. In some embodiments, cylinder 40 is not hollow. It should be appreciated that cylinder 40 may comprise any geometry suitable to compress hose 50 and express fluid therethrough. Waves containing kinetic energy enter wave chamber 20 through opening 22, the magnitude of said

waves being controlled by wave gate 26. Wave energy pushes cylinder 40 off its mooring proximate end 24A and down the ramped floor 24 thereby compressing hose 50. Water filling hose 50, which entered via intake valve 52, is expressed along hose 50 generally in direction A. One-way valve 54 ensures that water in hose 50 travel in only one direction, toward opening 30 and conduit 56 (generally direction A). Once cylinder 40 has been forced to the rear of wave chamber 20 (i.e., proximate end 24B) thereby expressing all of the water out of hose 50, it is drawn back to its original position proximate end 24A and opening 22 by springs 46A and 46B (not shown) so that the cycle can begin again. The movement of cylinder 40 in wave chamber 20 is shown by phantom lines in FIG. 1.

Water is expressed from hose 50 into conduit 56. Water travels through conduit 56 in a singular direction, due to one-way valves 58 and 60 arranged therein, and fills cistern 70. It should be appreciated that, although FIG. 1 shows only two one-way valves arranged in conduit 56, conduit 56 may comprise any number of one-way valves suitable to displace water from hose 50 to cistern 70, for example, one or more one-way valves. As shown, collected water 72 is held in cistern 70 until it is released through valve 74. Once released, water 72 travels through conduit 76 through turbine 78, thereby creating rotational movement of shaft 80. Turbine 78 is generally a machine for producing continuous power in which a wheel or rotor, typically fitted with vanes, is made to revolve by a moving flow of water or fluid, as is known in the art. Turbine 78 can, on its own, generate electrical power. In some embodiments, turbine 78 rotates shaft 80 which in turn activates flywheel 100 to produce and/or store energy (e.g., electrical power), as will be discussed in greater detail below. It should be appreciated that as wave energy capture device 10 pumps water from wave chamber 20 to cistern 70, the kinetic energy of waves is converted to potential energy. Subsequently, as water 72 is released through valve 74, potential energy is converted to kinetic energy.

FIG. 2 is a perspective view of wave energy capture device 210. Wave energy capture device 210 generally comprises float 220, shaft 230, and wheel 250.

Float 220 is a structure that is buoyant in water or other fluid. Float 220 is arranged in water 202 and can be any suitable shape, such as, for example, partially spherical-, spherical-, cylindrical-, rectangular prism-, cube-, triangular prism-, or pyramidal-shaped. The purpose of float 220 is to displace in directions C and D due to the waves of water 202.

Shaft 230 generally comprises end 232 and end 234. End 232 is connected to float 220. End 234 is connected to wheel 250. Shaft 230 comprises flexible portion 230A and stiff portion 230B. In some embodiments, shaft 230 is completely stiff. In some embodiments, shaft 230 is completely flexible. Shaft 230 is arranged on fulcrum 240. Fulcrum 240 engages shaft 230 at a point between end 232 and end 234. Fulcrum 240 is the point on which shaft 230 rests or is supported and on which shaft 230 pivots. Wave energy capture device 210 may further comprise oscillation restrictor 242. Oscillation restrictor 242 is arranged to limit the displacement of shaft 230. For example, when the magnitude of the waves of water 202 is too great, float 220 may be displaced at a level that may jeopardize the structural integrity of the components of wave energy capture device 210. Oscillation restrictor 242 is arranged to prevent such extreme displacement of float 220 and shaft 230.

Wheel 250 is connected to shaft 230 at end 234. End 234 is pivotably connected to wheel 250, such that wheel 250 can rotate as shaft 230 oscillates in directions C and D.

Wheel **250** is arranged to convert the oscillatory motion of float **220** and shaft **230** to rotational motion. As shown, end **234** is connected to wheel **250** such that as shaft **230** pivots about fulcrum **240**, wheel **250** rotates. In some embodiments, wheel **250** may comprise a freewheel or overrunning clutch (i.e., similar to those used in the pedal mechanism of a bicycle). In some embodiments, wheel **250** may comprise a ratchet device which allows wheel **250** to displace in a first circumferential direction but prevents wheel **250** from displacing in a second circumferential direction, opposite the first circumferential direction. In some embodiments, wheel **250** comprises a scotch tension wheel design.

Shaft **260** comprises end **262** and end **264**. End **262** is non-rotatably connected to wheel **250**. End **264** is connected to, for example, gearbox **270**. Wheel **250** rotates shaft **260**. Gearbox **270** transfers the rotational energy of shaft **260** to shaft **280**, which in turn, activates flywheel **100** to produce and/or store energy (e.g., electrical power), as will be discussed in greater detail below. It should be appreciated that shaft **260**, specifically end **264**, may be connected to any device suitable for producing energy (e.g., electrical power).

FIG. 3 is a perspective view of a wave energy capture device **310**. Wave energy capture device **310** generally comprises float **320**, shaft **330**, and shaft **380**.

Float **320** is a structure that is buoyant in water or other fluid. Float **320** is arranged in water **302** and can be any suitable shape, such as, for example, partially spherical, spherical-, cylindrical-, rectangular prism-, cube-, triangular prism-, or pyramidal-shaped. The purpose of float **320** is to displace in directions C and D due to the waves of water **302**.

Shaft **330** generally comprises end **332** and end **334**. End **332** is connected to float **320**. End **334** is connected to shaft **380**. Shaft **330** comprises flexible portion **330A** and stiff portion **330B**. In some embodiments, shaft **330** is completely stiff. In some embodiments, shaft **330** is completely flexible. Shaft **330** is arranged on fulcrum **340**. Fulcrum **340** engages shaft **330** at a point between end **332** and end **334**. Fulcrum **340** is the point on which shaft **330** rests or is supported and on which shaft **330** pivots. Wave energy capture device **310** may further comprise oscillation restrictor **342**. Oscillation restrictor **342** is arranged to limit the displacement of shaft **330**. For example, when the magnitude of the waves of water **302** is too great, float **320** may be displaced at a level that may jeopardize the structural integrity of the components of wave energy capture device **310**. Oscillation restrictor **342** is arranged to prevent such extreme displacement of float **320** and shaft **330**.

Shaft **380** is connected to shaft **330** at end **334**. End **334** is pivotably connected to shaft **380**, such that as shaft **330** oscillates in directions C and D, shaft **380** maintains its linear displacement action in directions C and D. Shaft **380** comprises threading **382** thereon. As shaft **380** is displaced in directions C and D, threading **382** interacts with threading on radially inward facing surface **104** of ring **102** of flywheel **100** to rotate flywheel **100** (flywheel, including radially inward facing surface **104** and ring **102**, will be discussed in greater detail below). The interaction between external threading **382** of shaft **380** and the internal threading of flywheel **100** creates a spiral plunger mechanism which activates/rotates flywheel **100** to produce and/or store energy (e.g., electrical power). This spiral plunger mechanism may be, for example, similar to a toy pump top. It should be appreciated that any mechanical device suitable for converting oscillatory motion into rotary motion may be used.

FIG. 4A is a cross-sectional view of wave energy capture device **410** in a relaxed state. FIG. 4B is a cross-sectional view of wave energy capture device **410** in a flexed state.

Wave energy capture device **410** generally comprises pump segments **420A-C** and hose **460**. In the embodiment shown, wave energy capture device **410** comprises pump segments **420A**, **420B**, and **420C**. It should be appreciated, however, that wave energy capture device **410** may comprise any suitable number of pump segments, for example, a plurality of pump segments. In some embodiments, wave energy capture device **410** only comprises one pump segment that is connected to a fixed object to create the piston movement required, as will be discussed in greater detail below. Wave energy capture device **410** is arranged in water **402**, either to float atop thereon, to be partially submerged therein, or to be fully submerged therein.

Pump segment **420A** comprises lateral wall **421A**, end **422A**, and end **426A**. End **422A** is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum **424A**. End **426A** is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum **428A**. It should be appreciated that ends **422A** and **426A** may comprise any suitable geometry for pivoting against adjacent pump segments or objects, for example, triangular. Lateral wall **421A** is arranged between ends **422A** and **426A**.

Pump segment **420A** further comprises piston **430A** arranged therein. Piston **430A** is connected to end **422A** via spring **432A**. Piston **430A** forms chamber **423A** along with lateral wall **421A** and end **426A**. Chamber **423A** is sealed and fluid may not enter or exit chamber **423A** except through valves **450A** and **452A**, as will be discussed in greater detail below. Pump segment **420A** further comprises cord **440A**, cord **470A**, and pulley **446A**. Cord **440A** comprises end **442A**, which is connected to piston **430A**, and end **444A**, which is connected to end **422B** of adjacent pump segment **420B**. Cord **470A** comprises end **474A**, which is connected to piston **430A**, and end **474A**, which is connected to end **422B** of adjacent pump segment **420B**. Pulley **446A** is rotatably connected to end **426A** and engages cord **440A** and cord **470A**. In some embodiments, pulley **446A** is non-rotatably connected to end **426A**. As shown, cord **440A** wraps at least partially around pulley **446A**, and cord **470A** wraps at least partially around pulley **446A**. Pulley **446A** allows pump segment **420A** to pivot about fulcrum **428A** relative to fulcrum **424B** of pump segment **420B**. In some embodiments, pump segment **420A** is pivotably connected to pump segment **420B** at fulcrums **428A** and **424B**.

Pump segment **420A** further comprises valves **450A** and **452A**. Valve **450A** is an inlet valve and is arranged to allow water **402** to enter chamber **423A** when wave energy capture device **410** is in the relaxed state or returning to the relaxed state from the flexed state. Valve **452A** is an outlet valve and is arranged to allow water from inside chamber **423A** to enter hose **460**. In some embodiments, valves **450A** and **452A** are one-way valves. As pump segment **420A** pivots with respect to pump segment **420B** (i.e., as in the flexed state of FIG. 4B), depending on the rotational direction of the pivot, either cord **440A** or **470A** will tighten about pulley **446A**, thereby pulling piston **430A** toward end **426A**. As piston **430A** displaces toward end **426A**, water in chamber **423A** is forced out of valve **452A** and into hose **460**. As shown in FIG. 4B, cord **440A** is tightened thus pulling piston **430A** toward end **426A**. As pump segment **420A** returns to a non-pivoted position (i.e., aligned as in the relaxed state of FIG. 4A), the tension of the tightened cords, either cord **440A** or cord **470A**, releases and spring **432A** displaces piston **430A** back toward end **422A**. As piston **430A** is displaced toward end **422A**, water **402** is sucked into chamber **423A** through valve **450A** via the negative pressure

created therein. As such, pump 420A is arranged to, using the wave energy of water 402, continuously pump water into hose 460.

Pump segment 420B comprises lateral wall 421B, end 422B, and end 426B. End 422B is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum 424B. End 426B is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum 428B. It should be appreciated that ends 422B and 426B may comprise any suitable geometry for pivoting against adjacent pump segments or objects, for example, triangular. Lateral wall 421B is arranged between ends 422B and 426B.

Pump segment 420B further comprises piston 430B arranged therein. Piston 430B is connected to end 422B via spring 432B. Piston 430B forms chamber 423B along with lateral wall 421B and end 426B. Chamber 423B is sealed and fluid may not enter or exit chamber 423B except through valves 450B and 452B, as will be discussed in greater detail below. Pump segment 420B further comprises cord 440B, cord 470B, and pulley 446B. Cord 440B comprises end 442B, which is connected to piston 430B, and end 444B, which is connected to end 422C of adjacent pump segment 420C. Cord 470B comprises end 474B, which is connected to piston 430B, and end 474B, which is connected to end 422C of adjacent pump segment 420C. Pulley 446B is rotatably connected to end 426B and engages cord 440B and cord 470B. In some embodiments, pulley 446B is non-rotatably connected to end 426B. As shown, cord 440B wraps at least partially around pulley 446B, and cord 470B wraps at least partially around pulley 446B. Pulley 446B allows pump segment 420B to pivot about fulcrum 428B relative to fulcrum 424C of pump segment 420C. In some embodiments, pump segment 420B is pivotably connected to pump segment 420C at fulcrums 428B and 424C.

Pump segment 420B further comprises valves 450B and 452B. Valve 450B is an inlet valve and is arranged to allow water 402 to enter chamber 423B when wave energy capture device 410 is in the relaxed state or returning to the relaxed state from the flexed state. Valve 452B is an outlet valve and is arranged to allow water from inside chamber 423B to enter hose 460. In some embodiments, valves 450B and 452B are one-way valves. As pump segment 420B pivots with respect to pump segment 420C (i.e., as in the flexed state of FIG. 4B), depending on the rotational direction of the pivot, either cord 440B or 470B will tighten about pulley 446B, thereby pulling piston 430B toward end 426B. As piston 430B displaces toward end 426B, water in chamber 423B is forced out of valve 452B and into hose 460. As shown in FIG. 4B, cord 470B is tightened thus pulling piston 430B toward end 426B. As pump segment 420B returns to a non-pivoted position (i.e., aligned as in the relaxed state of FIG. 4A), the tension of the tightened cords, either cord 440B or cord 470B, releases and spring 432B displaces piston 430B back toward end 422B. As piston 430B is displaced toward end 422B, water 402 is sucked into chamber 423B through valve 450B via the negative pressure created therein. As such, pump 420B is arranged to, using the wave energy of water 402, continuously pump water into hose 460.

Pump segment 420C comprises lateral wall 421C, end 422C, and end 426C. End 422C is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum 424C. End 426C is generally rounded, or partially circular or partially ellipsoidal, and comprises fulcrum 428C. It should be appreciated that ends 422C and 426C may comprise any suitable geometry for pivoting against

adjacent pump segments or objects, for example, triangular. Lateral wall 421C is arranged between ends 422C and 426C.

Pump segment 420C further comprises piston 430C arranged therein. Piston 430C is connected to end 422C via spring 432C. Piston 430C forms chamber 423C along with lateral wall 421C and end 426C. Chamber 423C is sealed and fluid may not enter or exit chamber 423C except through valves 450C and 452C, as will be discussed in greater detail below. Pump segment 420C further comprises cord 440C, cord 470C, and pulley 446C. Cord 440C comprises end 442C, which is connected to piston 430C, and end 444C, which is connected to the end of an adjacent pump segment, float, or fixed object (not shown). Cord 470C comprises end 474C, which is connected to piston 430C, and end 474C, which is connected to the end of an adjacent pump segment, float, or fixed object (not shown). Pulley 446C is rotatably connected to end 426C and engages cord 440C and cord 470C. In some embodiments, pulley 446C is non-rotatably connected to end 426C. As shown, cord 440C wraps at least partially around pulley 446C, and cord 470C wraps at least partially around pulley 446C. Pulley 446C allows pump segment 420C to pivot about fulcrum 428C relative to the fulcrum of the adjacent pump segment, float, or fixed object (not shown). In some embodiments, pump segment 420C is pivotably connected to the adjacent pump segment, float, or fixed object at fulcrum 428C.

Pump segment 420C further comprises valves 450C and 452C. Valve 450C is an inlet valve and is arranged to allow water 402 to enter chamber 423C when wave energy capture device 410 is in the relaxed state or returning to the relaxed state from the flexed state. Valve 452C is an outlet valve and is arranged to allow water from inside chamber 423C to enter hose 460. In some embodiments, valves 450C and 452C are one-way valves. As pump segment 420C pivots with respect to the adjacent pump segment, float, or fixed object (i.e., as in the flexed state of FIG. 4B), depending on the rotational direction of the pivot, either cord 440C or 470C will tighten about pulley 446C, thereby pulling piston 430C toward end 426C. As piston 430C displaces toward end 426C, water in chamber 423C is forced out of valve 452C and into hose 460. As shown in FIG. 4B, cord 440C is tightened thus pulling piston 430C toward end 426C. As pump segment 420C returns to a non-pivoted position (i.e., aligned as in the relaxed state of FIG. 4A), the tension of the tightened cords, either cord 440C or cord 470C, releases and spring 432C displaces piston 430C back toward end 422C. As piston 430C is displaced toward end 422C, water 402 is sucked into chamber 423C through valve 450C via the negative pressure created therein. As such, pump 420C is arranged to, using the wave energy of water 402, continuously pump water into hose 460.

Hose 460 is arranged adjacent to pump segments 420A-C. Hose 460 is an elastomeric hose and is fluidly connected to pump segment 420A at valve 452A, pump segment 420B at valve 452B, and pump segment 420C at valve 452C. As previously discussed, pump segment 420A pumps water into hose 460 via valve 452A, pump segment 420B pumps water into hose 460 via valve 452B, and pump segment 420C pumps water into hose 460 via valve 452C. Hose 460 comprises one or more one-way valves arranged therein. As shown, hose 460 comprises one-way valves 462, 464, and 466. One-way valves 462, 464, and 466 are arranged to displace water in hose 460 in generally one direction therealong (e.g., in direction E as shown in FIG. 4B). In some embodiments, hose 460 is at least partially rigid.

Water in hose 460 is expressed in direction E into, for example, conduit 56 as shown in FIG. 1. Water travels

through conduit 56 in a singular direction, due to one-way valves 58 and 60 arranged therein, and fills cistern 70. It should be appreciated that, although FIG. 1 shows only two one-way valves arranged in conduit 56, conduit 56 may comprise any number of one-way valves suitable to displace water from hose 460 to cistern 70, for example, one or more one-way valves. As shown, collected water 72 is held in cistern 70 until it is released through valve 74. Once released, water 72 travels through conduit 76 through turbine 78, thereby creating rotational movement of shaft 80. Turbine 78 is generally a machine for producing continuous power in which a wheel or rotor, typically fitted with vanes, is made to revolve by a moving flow of water or fluid, as is known in the art. Turbine 78 can, on its own, generate electrical power. In some embodiments, turbine 78 rotates shaft 80 which in turn activates flywheel 100 to produce and/or store energy (e.g., electrical power), as will be discussed in greater detail below. It should be appreciated that as wave energy capture device 410 pumps water from pump segments 420A-C to cistern 70, the kinetic energy of waves is converted to potential energy. Subsequently, as water 72 is released through valve 74, potential energy is converted to kinetic energy.

FIG. 5A is an elevational view of wave energy capture device 510 in a first position. FIG. 5B is an elevational view of wave energy capture device 510 in a second position. FIG. 5C is an elevational view of wave energy capture device 510 in a third position. Wave energy capture device 510 generally comprises wave fan 520, shaft 530, and roller 540. Wave energy capture device 510 is arranged to capture wave energy on the ocean (or other body of water) floor.

Wave fan 520 is arranged to catch wave energy. Shaft 530 comprises end 532, which is connected to wave fan 520, and end 534, which is connected to roller 540. Shaft 530 is connected to a rotary pivot point at pivot 536. Pivot 536 may include a bearing. Shaft 530 is arranged to rotate about pivot 536 to displace water from hose 550. Roller 540 is rotatably connected to end 534.

Hose 550 is arranged along the ocean floor generally below wave energy capture device 510. Hose 550 is an elastomeric hose comprising intake valve 556. Hose 550 comprises one or more one-way valves arranged therein. As shown, hose 550 comprises one-way valves 552 and 554. One-way valves 552 and 554 are arranged to displace water in hose 550 in direction H. In some embodiments, hose 550 is at least partially rigid.

As shown in FIG. 5A, wave energy capture device 510 is positioned in a first position, or the primed position. A wave or current catches wave fan 520 and displaces wave fan 520, shaft 530, and roller 540 in circumferential direction F. In FIG. 5B, wave energy capture device 510 is in the second position or engaged position. As shown, roller 540 is engaged with hose 550. As shaft 530 is rotated in circumferential direction F, roller 540 compresses hose 550 expressing the water therein in direction H. The water in hose 550 is expressed in direction H through one-way valve 554. As shown in FIG. 5C, wave energy capture device 510 is in third position or the fired position. After roller 540 has expressed water from hose 550 through one-way valve 554 in direction H, the negative pressure created in elastomeric hose 550 causes water to be sucked in through intake valve 556 and one-way valve 552, thereby re-priming hose 550.

Water in hose 550 is expressed in direction H into, for example, conduit 56 as shown in FIG. 1. Water travels through conduit 56 in a singular direction, due to one-way valves 58 and 60 arranged therein, and fills cistern 70. It should be appreciated that, although FIG. 1 shows only two

one-way valves arranged in conduit 56, conduit 56 may comprise any number of one-way valves suitable to displace water from hose 550 to cistern 70, for example, one or more one-way valves. As shown, collected water 72 is held in cistern 70 until it is released through valve 74. Once released, water 72 travels through conduit 76 through turbine 78, thereby creating rotational movement of shaft 80. Turbine 78 is generally a machine for producing continuous power in which a wheel or rotor, typically fitted with vanes, is made to revolve by a moving flow of water or fluid, as is known in the art. Turbine 78 can, on its own, generate electrical power. In some embodiments, turbine 78 rotates shaft 80 which in turn activates flywheel 100 to produce and/or store energy (e.g., electrical power), as will be discussed in greater detail below. It should be appreciated that as wave energy capture device 510 pumps water from hose 550 to cistern 70, the kinetic energy of waves is converted to potential energy. Subsequently, as water 72 is released through valve 74, potential energy is converted to kinetic energy. In some embodiments, one or more wave energy capture devices 510 may be arranged along one hose to pump water into cistern 70. In some embodiments, a plurality of wave energy devices arranged along a plurality of hoses are used to pump water into cistern 70.

FIG. 6A is an elevational view of wave energy capture device 610. FIG. 6B is a partial cross-sectional view of wave energy capture device 610. Wave energy capture device 610 generally comprises wave fan 620, shaft 630, and peristaltic rotor 660. Wave energy capture device 610 is arranged to capture wave energy on the ocean (or other body of water) floor.

Wave fan 620 is arranged to catch wave energy. Shaft 630 comprises end 632, which is connected to wave fan 620, and end 634, which is connected to peristaltic rotor 660. Shaft 630 is rotatably connected to pivot 636 at end 634. Similarly, peristaltic rotor 660 is rotatably connected to pivot 636. Both shaft 630 and peristaltic rotor 660 rotate about pivot 636. Pivot 636 may include a bearing. Shaft 630 is arranged to rotate about pivot 636 and rotate peristaltic rotor 660 in, for example, circumferential direction F. As peristaltic rotor 660 rotates, protrusions 660A-C engage hose 650 and displace water from hose 550.

As shown in FIG. 6B, wave energy capture device 610 comprises ratchet mechanism 640. Ratchet mechanism 640 comprises ratchet 662, catch 666, and pawl 668. Peristaltic rotor 660 is non-rotatably connected to ratchet 662, which rotates about pivot 636. Ratchet 662 is rotatably connected to pivot 636. Ratchet 662 comprises a plurality of teeth 664 arranged thereon. Catch 666 is rotatably connected to shaft 630 proximate end 634. Catch 666 is arranged to engage teeth 664 such that shaft 630 can rotate ratchet in circumferential direction F, but not in circumferential direction G. However, shaft 630 is capable of displacing in circumferential direction G relative to ratchet 662. Pawl 668 is arranged to engage teeth 664 such that ratchet can rotate only in circumferential direction F.

Hose 650 is arranged along the ocean floor generally below wave energy capture device 610. Hose 650 is an elastomeric hose comprising intake valve 656. Hose 650 comprises one or more one-way valves arranged therein. As shown, hose 650 comprises one-way valves 652 and 654. One-way valves 652 and 654 are arranged to displace water in hose 650 in direction H. In some embodiments, hose 650 is at least partially rigid.

As a wave or current catches wave fan 620 and displaces wave fan 620 and shaft 630 in circumferential direction F, shaft 630, specifically catch 666, engages ratchet 662 and

rotates ratchet 662 and thus peristaltic rotor 660 in circumferential direction F. As such, protrusions 660A-C rotate about pivot 636 to engage hose 650 and express the water therein in direction H. The water in hose 650 is expressed in direction H through one-way valve 654. After peristaltic rotor 660 has expressed water from hose 650 through one-way valve 654 in direction H, the negative pressure created in elastomeric hose 650 causes water to be sucked in through intake valve 656 and one-way valve 652, thereby re-priming hose 650. After the wave or current has passed, wave fan 620 and shaft 630 return to an upright position. In some embodiments, in order to return to its starting upright position, shaft 630 may be connected to a spring that returns wave energy capture device 610 to its original starting position. In some embodiments, in order to return to its starting upright position, wave fan 620 may comprise a float that pulls it and shaft 630 upright after displacement.

Water in hose 650 is expressed in direction H into, for example, conduit 56 as shown in FIG. 1. Water travels through conduit 56 in a singular direction, due to one-way valves 58 and 60 arranged therein, and fills cistern 70. It should be appreciated that, although FIG. 1 shows only two one-way valves arranged in conduit 56, conduit 56 may comprise any number of one-way valves suitable to displace water from hose 650 to cistern 70, for example, one or more one-way valves. As shown, collected water 72 is held in cistern 70 until it is released through valve 74. Once released, water 72 travels through conduit 76 through turbine 78, thereby creating rotational movement of shaft 80. Turbine 78 is generally a machine for producing continuous power in which a wheel or rotor, typically fitted with vanes, is made to revolve by a moving flow of water or fluid, as is known in the art. Turbine 78 can, on its own, generate electrical power. In some embodiments, turbine 78 rotates shaft 80 which in turn activates flywheel 100 to produce and/or store energy (e.g., electrical power), as will be discussed in greater detail below. It should be appreciated that as wave energy capture device 610 pumps water from hose 650 to cistern 70, the kinetic energy of waves is converted to potential energy. Subsequently, as water 72 is released through valve 74, potential energy is converted to kinetic energy. In some embodiments, one or more wave energy capture devices 610 may be arranged along one hose to pump water into cistern 70. In some embodiments, a plurality of wave energy devices arranged along a plurality of hoses are used to pump water into cistern 70.

FIG. 7 is a perspective view of flywheel 100. FIG. 8 is an elevational view of flywheel 100. Flywheel 100 is a concentric ring flywheel that is connected to shaft 80, 280, 380. Flywheel 100 generally comprises rings 102, 112, 122, and 132, all concentrically arranged about shaft 80, 280, 380. It should be appreciated that flywheel 100 may have any suitable number of rings, and that this disclosure should not be limited to the use of just four rings as shown. Rings 102, 112, 122, and 132 may be arranged on magnetic bearings 160. In some embodiments, rings 102, 112, 122, and 132 have planar top surfaces and planar bottom surfaces, the planar top surfaces being parallel to the planar bottom surfaces. In some embodiments, rings 102, 112, 122, and 132 have planar top surfaces and planar bottom surfaces, the planar bottom surfaces being non-parallel to the planar top surfaces (e.g., angled). In some embodiments, rings 102, 112, 122, and 132 have planar top surfaces and curvilinear bottom surfaces, as will be discussed in greater detail below. Additionally, rings 102, 112, 122, and 132 may be solid, hollow, or partially hollow.

Ring 102 comprises radially inward facing surface 104 and radially outward facing surface 106. Radially inward facing surface 104 is non-rotatably connected to shaft 80, 280. In some embodiments, and as described with respect to FIG. 3, radially inward facing surface 104 is threadably engaged with shaft 380. For example, radially inward facing surface 104 comprises threading which engages threading 382 of shaft 380.

Ring 112 comprises radially inward facing surface 114 and radially outward facing surface 116. Ring 112 is arranged radially outward from ring 102 with space 110 arranged radially therebetween. Ring 112 is arranged to non-rotatably engage ring 102 such that rings 102 and 112 can be rotatably locked and unlocked. Specifically, radially inward facing surface 114 is arranged to engage radially outward facing surface 106, for example, via one or more rollers, detents, connectors, ramps, etc. In some embodiments, clutch connectors 108A-H are arranged between radially inward facing surface 114 and radially outward facing surface 106. Clutch connectors 108A-H, when activated, non-rotatably connect ring 112 with ring 102. It should be appreciated that any suitable means for non-rotatably connecting ring 112 with ring 102 may be used. In some embodiments, clutch connectors 108A-H are rollers and radially inward facing surface 114 comprises a plurality of ramps such that, when ring 102 reaches a preset rotational speed the rollers run up the ramps and non-rotatably connect ring 112 with ring 102. In such a purely mechanical clutch connection method, once the rotational speed of ring 102 drops below the preset rotational speed, the rollers disengage and ring 112 disengages ring 102 and continues to rotate unencumbered by the lapse in energy input. In some embodiments, clutch connectors 108A-H are connected to radially outward facing surface 106 and can be displaced radially outward to lock in with contact points arranged on radially inward facing surface 114 to non-rotatably connect ring 112 with ring 102. This radial displacement may occur automatically once ring 102 reaches a certain rotational speed via either a mechanical mechanism or an electronic actuation mechanism guided by a computer and wireless communication (e.g., Bluetooth® communication, infrared radiation, radio waves, etc.). In such an electronic version of clutch engagement between rings 112 and 102, a computer may calculate the optimal rotational speed (e.g., RPM) to transfer energy between rings based on rotational speed of ring 102 (and shaft 80, 280) and the radius and mass of rings 102 and 112. The computer may then activate the electronic clutch mechanism between rings 102 and 112. Using a computer system, both the mass and radius of flywheel 100 can be controlled and varied almost instantaneously in order to maintain a constant rate of rotational speed to ensure that the wave energy captured can be converted to a consistent, stable, and accessible energy source. For example, flywheel 100 could be maintained at an optimal rotational speed of 1,800 RPM by transferring energy from an outer ring inward or from an inner ring outward.

Ring 122 comprises radially inward facing surface 124 and radially outward facing surface 126. Ring 122 is arranged radially outward from ring 112 with space 120 arranged radially therebetween. Ring 122 is arranged to non-rotatably engage ring 112 such that rings 112 and 122 can be rotatably locked and unlocked. Specifically, radially inward facing surface 124 is arranged to engage radially outward facing surface 116, for example, via one or more rollers, detents, connectors, ramps, etc. In some embodiments, clutch connectors 118A-H are arranged between radially inward facing surface 124 and radially outward

facing surface 116. Clutch connectors 118A-H, when activated, non-rotatably connect ring 122 with ring 112. It should be appreciated that any suitable means for non-rotatably connecting ring 122 with ring 112 may be used. In some embodiments, clutch connectors 118A-H are rollers and radially inward facing surface 124 comprises a plurality of ramps such that, when ring 112 reaches a preset rotational speed the rollers run up the ramps and non-rotatably connect ring 122 with ring 112. In such a purely mechanical clutch connection method, once the rotational speed of ring 112 drops below the preset rotational speed, the rollers disengage and ring 122 disengages ring 112 and continues to rotate unencumbered by the lapse in energy input. In some embodiments, clutch connectors 118A-H are connected to radially outward facing surface 116 and can be displaced radially outward to lock in with contact points arranged on radially inward facing surface 124 to non-rotatably connect ring 122 with ring 112. This radial displacement may occur automatically once ring 112 reaches a certain rotational speed via either a mechanical mechanism or an electronic actuation mechanism guided by a computer and wireless communication (e.g., Bluetooth® communication, infrared radiation, radio waves, etc.). In such an electronic version of clutch engagement between rings 122 and 112, a computer may calculate the optimal rotational speed (e.g., RPM) to transfer energy between rings based on rotational speed of ring 112 (and ring 102 and shaft 80, 280) and the radius and mass of rings 112 and 122. The computer may then activate the electronic clutch mechanism between rings 112 and 122. Using a computer system, both the mass and radius of flywheel 100 can be controlled and varied almost instantaneously in order to maintain a constant rate of rotational speed to ensure that the wave energy captured can be converted to a consistent, stable, and accessible energy source. For example, flywheel 100 could be maintained at an optimal rotational speed of 1,800 RPM by transferring energy from an outer ring inward or from an inner ring outward.

Ring 132 comprises radially inward facing surface 134 and radially outward facing surface 136. Ring 132 is arranged radially outward from ring 122 with space 130 arranged radially therebetween. Ring 132 is arranged to non-rotatably engage ring 122 such that rings 122 and 132 can be rotatably locked and unlocked. Specifically, radially inward facing surface 134 is arranged to engage radially outward facing surface 126, for example, via one or more rollers, detents, connectors, ramps, etc. In some embodiments, clutch connectors 128A-H are arranged between radially inward facing surface 134 and radially outward facing surface 126. Clutch connectors 128A-H, when activated, non-rotatably connect ring 132 with ring 122. It should be appreciated that any suitable means for non-rotatably connecting ring 132 with ring 122 may be used. In some embodiments, clutch connectors 128A-H are rollers and radially inward facing surface 134 comprises a plurality of ramps such that, when ring 122 reaches a preset rotational speed the rollers run up the ramps and non-rotatably connect ring 132 with ring 122. In such a purely mechanical clutch connection method, once the rotational speed of ring 122 drops below the preset rotational speed, the rollers disengage and ring 132 disengages ring 122 and continues to rotate unencumbered by the lapse in energy input. In some embodiments, clutch connectors 128A-H are connected to radially outward facing surface 126 and can be displaced radially outward to lock in with contact points arranged on radially inward facing surface 134 to non-rotatably connect ring 132 with ring 122. This radial displacement may occur

automatically once ring 122 reaches a certain rotational speed via either a mechanical mechanism or an electronic actuation mechanism guided by a computer and wireless communication (e.g., Bluetooth® communication, infrared radiation, radio waves, etc.). In such an electronic version of clutch engagement between rings 132 and 122, a computer may calculate the optimal rotational speed (e.g., RPM) to transfer energy between rings based on rotational speed of ring 122 (and ring 102, ring 112, and shaft 80, 280) and the radius and mass of rings 122 and 132. The computer may then activate the electronic clutch mechanism between rings 122 and 132. Using a computer system, both the mass and radius of flywheel 100 can be controlled and varied almost instantaneously in order to maintain a constant rate of rotational speed to ensure that the wave energy captured can be converted to a consistent, stable, and accessible energy source. For example, flywheel 100 could be maintained at an optimal rotational speed of 1,800 RPM by transferring energy from an outer ring inward or from an inner ring outward.

In some embodiments, flywheel 100 is arranged on magnetic bearings and arranged in a vacuum to increase efficiency. In some embodiments, shaft 80, 280 is connected to ring 102, specifically radially inward facing surface 104, via clutch connectors (e.g., a free wheel clutch). In times of low wave energy input, shaft 80, 280 may disconnect from flywheel 100 to limit frictional energy loss. In times of high wave energy input, energy can be progressively transferred to the larger, heavier outer rings having greater angular momentum and hence greater energy generation/storage. By arranging rotors adjacent to rings 102, 112, 122, and 132 (e.g., below the bottom surfaces of the rings), flywheel 100 can provide for energy storage as well as conversion of kinetic energy into electrical energy. As previously discussed, flywheel 100 stores kinetic energy (energy of mass in motion) by constantly spinning a compact rotor in a low-friction environment. The stored kinetic energy of flywheel 100 is proportional to the mass of its rotor, the square of its radius, and the square of its rotational speed (e.g., RPM). Flywheel 100 is capable of being adjusted by altering factors such as, increasing the rotational speed of the rotor (i.e., by engaging outer rings), which increases stored energy, and increasing the mass of the rotor (i.e., by engaging outer rings), which increases stored energy. Flywheel 100, which acts as a rotor or armature, creates electromagnetic induction by spinning or rotating inside or adjacent to a stator of opposing magnetism. The stator is generally a stationary magnetic field with large copper windings. As is known in the art, is the rotation of the electromagnetic armature/rotor (i.e., flywheel) relative to the stationary magnetic field (i.e., the stator) which produces electrical current. The present disclosure harnesses wave energy to rotate flywheel 100, the rotational velocity of which can be adjusted by engaging/disengaging the concentric rings, and generate electrical current. It should be appreciated that flywheel 100 can be used with wind energy capture devices in addition to wave energy capture devices.

FIG. 9A is a cross-sectional view of an embodiment of flywheel 100 taken generally along line 9-9 in FIG. 8, in a first state. In the embodiment shown, rings 102, 112, 122, and 132 comprise curvilinear bottom surfaces. Each of rings 102, 112, 122, and 132 are hollow and comprise one or more ridges therein. Additionally, rings 102, 112, 122, and 132 may further include fluid 150 therein. In the first state, flywheel 100 is not rotating, but rather is at rest.

As shown, ring 102 comprises ridges 107A and 107B arranged on radially outward facing surface 106. Radially

outward facing surface **106** may be completely parabolic from radially inward facing surface **104**, completely linear from radially inward facing surface **104**, or comprise a parabolic section connected to radially inward facing surface **104** connected to a linear portion leading to the top surface. Ring **102** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **102**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **104**, due to gravity.

Ring **112** comprises ridges **117A** and **117B** arranged on radially outward facing surface **116**. Radially outward facing surface **116** may be completely parabolic from radially inward facing surface **114**, completely linear from radially inward facing surface **114**, or comprise a parabolic section connected to radially inward facing surface **114** connected to a linear portion leading to the top surface. Ring **112** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **112**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **114**, due to gravity.

Ring **122** comprises ridges **127A** and **127B** arranged on radially outward facing surface **126**. Radially outward facing surface **126** may be completely parabolic from radially inward facing surface **124**, completely linear from radially inward facing surface **124**, or comprise a parabolic section connected to radially inward facing surface **124** connected to a linear portion leading to the top surface. Ring **122** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **122**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **124**, due to gravity.

Ring **132** comprises ridges **137A** and **137B** arranged on radially outward facing surface **136**. Radially outward facing surface **136** may be completely parabolic from radially inward facing surface **134**, completely linear from radially inward facing surface **134**, or comprise a parabolic section connected to radially inward facing surface **134** connected to a linear portion leading to the top surface. Ring **132** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **132**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **134**, due to gravity.

FIG. **9B** is a cross-sectional view of flywheel **100** taken generally along line **9-9** in FIG. **8**, with rings **102**, **112**, **122**, and **132** having curvilinear bottom surfaces, in a second state. In the second state, flywheel **100** is rotating, with all of clutch connectors **108A-H**, **118A-H**, and **128A-H** engaged to rotatably lock rings **102**, **112**, **122**, and **132**, at a less than maximum rotational speed. As shown, fluid **150** is displaced up and radially outward along the respective radially outward facing surfaces. In ring **102**, fluid **150** is displaced along radially outward facing surface **106** to the level of ridge **107A**. In ring **112**, fluid **150** is displaced along radially outward facing surface **116** to the bottom of ridge **117B**. In ring **122**, fluid **150** is displaced along radially outward facing surface **126** to the top of ridge **127B**. In ring **132**, fluid **150** is displaced along radially outward facing surface **136** up past ridge **137B**. Fluid in the outer rings will exhibit a greater displacement along the radially outward facing surface than that of the inner rings because, when rotationally locked, the outer rings rotate at a higher angular velocity than that of the inner rings.

FIG. **9C** is a cross-sectional view of flywheel **100** taken generally along line **9-9** in FIG. **8**, with rings **102**, **112**, **122**, and **132** having curvilinear bottom surfaces, in a third state. In the third state, flywheel **100** is rotating, with all of clutch connectors **108A-H**, **118A-H**, and **128A-H** engaged to rotatably lock rings **102**, **112**, **122**, and **132**, at a maximum rotational speed. As shown, fluid **150** is further displaced up and radially outward along the respective radially outward facing surfaces. In ring **102**, fluid **150** is displaced along radially outward facing surface **106** to the bottom of ridge **107B**. In ring **112**, fluid **150** is displaced along radially outward facing surface **116** to the top of ridge **117B**. In ring **122**, fluid **150** is displaced along radially outward facing surface **126** up past ridge **127B**. In ring **132**, fluid **150** is displaced along radially outward facing surface **136** up to the top surface of ring **132**.

FIG. **10A** is a cross-sectional view of an embodiment of flywheel **100** taken generally along line **10-10** in FIG. **8**, in a first state. In the embodiment shown, rings **102**, **112**, **122**, and **132** comprise curvilinear bottom surfaces. Each of rings **102**, **112**, **122**, and **132** are hollow and comprise one or more walls or gates therein. Additionally, rings **102**, **112**, **122**, and **132** may further include fluid **150** therein. In the first state, flywheel **100** is not rotating, but rather is at rest.

As shown, ring **102** comprises walls **109A** and **109B** extending between the top surface and radially outward facing surface **106**. Radially outward facing surface **106** may be completely parabolic from radially inward facing surface **104**, completely linear from radially inward facing surface **104**, or comprise a parabolic section connected to radially inward facing surface **104** connected to a linear portion leading to the top surface. Ring **102** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **102**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **104**, due to gravity. Neither of walls **109A** or **109B** is open to allow fluid **150** to displace radially outward within ring **102**.

Ring **112** comprises walls **119A** and **119B** extending between the top surface and radially outward facing surface **116**. Radially outward facing surface **116** may be completely parabolic from radially inward facing surface **114**, completely linear from radially inward facing surface **114**, or comprise a parabolic section connected to radially inward facing surface **114** connected to a linear portion leading to the top surface. Ring **112** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **112**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **114**, due to gravity. Neither of walls **119A** or **119B** is open to allow fluid **150** to displace radially outward within ring **112**.

Ring **122** comprises walls **129A** and **129B** extending between the top surface and radially outward facing surface **126**. Radially outward facing surface **126** may be completely parabolic from radially inward facing surface **124**, completely linear from radially inward facing surface **124**, or comprise a parabolic section connected to radially inward facing surface **124** connected to a linear portion leading to the top surface. Ring **122** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **122**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward

facing surface **124**, due to gravity. Neither of walls **129A** or **129B** is open to allow fluid **150** to displace radially outward within ring **122**.

Ring **132** comprises walls **139A** and **139B** extending between the top surface and radially outward facing surface **136**. Radially outward facing surface **136** may be completely parabolic from radially inward facing surface **134**, completely linear from radially inward facing surface **134**, or comprise a parabolic section connected to radially inward facing surface **134** connected to a linear portion leading to the top surface. Ring **132** comprises fluid **150**, which may be, for example, water, mercury, or any other suitable fluid for controlling and/or increasing angular velocity with ring **132**. In the first state, as shown in FIG. **9A**, fluid **150** is drawn down and radially inward toward radially inward facing surface **134**, due to gravity. Neither of walls **139A** or **139B** is open to allow fluid **150** to displace radially outward within ring **132**.

FIG. **10B** is a cross-sectional view of flywheel **100** taken generally along line **10-10** in FIG. **8**, with rings **102**, **112**, **122**, and **132** having curvilinear bottom surfaces, in a second state. In the second state, flywheel **100** is rotating, with all of clutch connectors **108A-H**, **118A-H**, and **128A-H** engaged to rotatably lock rings **102**, **112**, **122**, and **132**, at a less than maximum rotational speed. As shown, fluid **150** is displaced up and radially outward along the respective radially outward facing surfaces. In ring **102**, wall **109A** is open allowing fluid **150** to displace along radially outward facing surface **106**. Wall **109A** may open via the opening of a valve or window, either electronically or mechanically. In ring **112**, wall **119A** is open allowing fluid **150** to displace along radially outward facing surface **116**. Wall **109A** may open via the opening of a valve or window, either electronically or mechanically. In ring **122**, wall **129A** is open allowing fluid **150** to displace along radially outward facing surface **126**. Wall **129A** may open via the opening of a valve or window, either electronically or mechanically. In ring **132**, wall **139A** is open allowing fluid **150** to displace along radially outward facing surface **136**. Wall **139A** may open via the opening of a valve or window, either electronically or mechanically. Fluid in the outer rings will exhibit a greater displacement along the radially outward facing surface than that of the inner rings because, when rotationally locked, the outer rings rotate at a higher angular velocity than that of the inner rings.

FIG. **10C** is a cross-sectional view of flywheel **100** taken generally along line **10-10** in FIG. **8**, with rings **102**, **112**, **122**, and **132** having curvilinear bottom surfaces, in a third state. In the third state, flywheel **100** is rotating, with all of clutch connectors **108A-H**, **118A-H**, and **128A-H** engaged to rotatably lock rings **102**, **112**, **122**, and **132**, at a maximum rotational speed. As shown, fluid **150** is further displaced up and radially outward along the respective radially outward facing surfaces. In ring **102**, both of walls **109A** and **109B** are open allowing fluid **150** to displace along radially outward facing surface **106**. Like wall **109A**, wall **109B** may open via the opening of a valve or window, either electronically or mechanically. In ring **112**, both of walls **119A** and **119B** are open allowing fluid **150** to displace along radially outward facing surface **116**. Like wall **119A**, wall **119B** may open via the opening of a valve or window, either electronically or mechanically. In ring **122**, both of walls **129A** and **129B** are open allowing fluid **150** to displace along radially outward facing surface **126**. Like wall **129A**, wall **129B** may open via the opening of a valve or window, either electronically or mechanically. In ring **132**, both of walls **139A** and **139B** are open allowing fluid **150** to displace along radially

outward facing surface **136**. Like wall **139A**, wall **139B** may open via the opening of a valve or window, either electronically or mechanically.

It should be appreciated that valves may be arranged in the walls of the respective rings. These valves may be electronically controlled. Specifically, the valves may be opened when wave energy is large enough to provide a high angular velocity to flywheel **100**. The valves may be operated mechanically, such that, when the pressure of fluid **150** against the valves reaches a predetermined threshold, the valves automatically open and allow fluid to flow into the next compartment within the ring. The addition of the walls within the individual rings of flywheel **100** provide even better control of angular velocity and the transfer of mass radially within flywheel **100**.

It will be appreciated that various aspects of the disclosure above and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

REFERENCE NUMERALS

- 2** Water
- 10** Wave energy capture device
- 20** Chamber
- 22** Opening
- 24** Floor
- 24A** End
- 24B** End
- 26** Wave gate
- 28** Section
- 30** Opening
- 32** Rail
- 40** Cylinder, object, float
- 42** Radially outward facing surface
- 44A** Point
- 44B** Point (not shown)
- 46A** Spring
- 46B** Spring (not shown)
- 50** Hose
- 50A** Portion
- 52** Intake valve
- 54** One-way valve
- 56** Conduit
- 58** One-way valve
- 60** One-way valve
- 62** One-way valve
- 70** Cistern
- 72** Water
- 74** Valve
- 76** Conduit
- 78** Turbine
- 80** Shaft
- 100** Flywheel
- 102** Ring
- 104** Radially inward facing surface
- 106** Radially outward facing surface
- 107A** Ridge
- 107B** Ridge
- 108A** Clutch connector
- 108B** Clutch connector
- 108C** Clutch connector
- 108D** Clutch connector

108E Clutch connector
 108F Clutch connector
 108G Clutch connector
 10811 Clutch connector
 109A Wall
 109B Wall
 110 Space
 112 Ring
 114 Radially inward facing surface
 116 Radially outward facing surface
 117A Ridge
 117B Ridge
 118A Clutch connector
 118B Clutch connector
 118C Clutch connector
 118D Clutch connector
 118E Clutch connector
 118F Clutch connector
 118G Clutch connector
 118H Clutch connector
 119A Wall
 119B Wall
 120 Space
 122 Ring
 124 Radially inward facing surface
 126 Radially outward facing surface
 127A Ridge
 127B Ridge
 128A Clutch connector
 128B Clutch connector
 128C Clutch connector
 128D Clutch connector
 128E Clutch connector
 128F Clutch connector
 128G Clutch connector
 128H Clutch connector
 129A Wall
 129B Wall
 130 Space
 132 Ring
 134 Radially inward facing surface
 136 Radially outward facing surface
 137A Ridge
 137B Ridge
 139A Wall
 139B Wall
 150 Fluid
 160 Magnetic bearings
 202 Water
 210 Wave energy capture device
 220 Float
 230 Shaft
 230A Portion
 230B Portion
 232 End
 234 End
 240 Fulcrum
 242 Oscillation restrictor
 250 Wheel
 260 Shaft
 262 End
 264 End
 270 Gearbox
 280 Shaft
 302 Water
 310 Wave energy capture device
 320 Float

330 Shaft
 330A Portion
 330B Portion
 332 End
 5 334 End
 340 Fulcrum
 342 Oscillation restrictor
 380 Shaft
 382 Threading
 10 402 Water
 410 Wave energy capture device
 420A Pump segment
 420B Pump segment
 420C Pump segment
 15 421A Lateral wall
 421B Lateral wall
 421C Lateral wall
 422A End
 422B End
 20 422C End
 423A Chamber
 423B Chamber
 423C Chamber
 424A Fulcrum
 25 424B Fulcrum
 424C Fulcrum
 426A End
 426B End
 426C End
 30 428A Fulcrum
 428B Fulcrum
 428C Fulcrum
 430A Piston
 430B Piston
 35 430C Piston
 432A Spring
 432B Spring
 432C Spring
 440A Cord
 40 440B Cord
 440C Cord
 442A End
 442B End
 442C End
 45 444A End
 444B End
 444C End
 446A Pulley
 446B Pulley
 50 446C Pulley
 450A Valve
 450B Valve
 450C Valve
 452A Valve
 55 452B Valve
 452C Valve
 460 Hose
 462 One-way valve
 464 One-way valve
 60 466 One-way valve
 470A Cord
 470B Cord
 470C Cord
 472A End
 65 472B End
 472C End
 474A End

- 474B End
- 474C End
- 510 Wave energy capture device
- 520 Wave fan
- 530 Shaft
- 532 End
- 534 End
- 536 Pivot
- 540 Roller
- 550 Hose
- 552 One-way valve
- 554 One-way valve
- 556 Intake valve
- 610 Wave energy capture device
- 620 Wave fan
- 630 Shaft
- 632 End
- 634 End
- 636 Pivot
- 640 Ratchet mechanism
- 650 Hose
- 652 One-way valve
- 654 One-way valve
- 656 Intake valve
- 660 Peristaltic rotor
- 660A Protrusion
- 660B Protrusion
- 660C Protrusion
- 662 Ratchet
- 664 Teeth
- 666 Catch
- 668 Pawl
- A Direction
- B Direction
- C Direction
- D Direction
- E Direction
- F Direction
- G Direction
- H Direction

What is claimed is:

1. A concentric ring flywheel arranged to interact with at least one stator for generating electrical current, the concentric ring flywheel comprising:

- a shaft;
- a plurality of rings, the plurality of rings including at least:
 - a first ring, including:
 - a first radially inward facing surface arranged to connect with the shaft; and,
 - a first radially outward facing surface;
 - a second ring arranged concentrically around the first ring, the second ring including:
 - a second radially inward facing surface; and,
 - a second radially outward facing surface, wherein a first space is arranged radially between the first radially outward facing surface and the second radially inward facing surface; and,
- one or more first clutch connectors arranged in the first space to non-rotatably connect the second ring and the first ring;

wherein:

- when the first ring rotates at a first rotational speed, the first ring and the second ring are rotatable with respect to each other; and,
- when the first ring rotates at a second rotational speed, the one or more first clutch connectors non-rotatably connect the first ring and the second ring.

2. The concentric ring flywheel as recited in claim 1, wherein at least one of the plurality of rings is hollow.

3. The concentric ring flywheel as recited in claim 1, wherein at least one of the plurality of rings is hollow and comprises fluid therein.

4. The concentric ring flywheel as recited in claim 1, wherein at least one of the plurality of rings is hollow and comprises:

- fluid arranged therein; and,
- one or more ridges.

5. The concentric ring flywheel as recited in claim 1, wherein at least one of the plurality of rings is hollow and comprises:

- fluid arranged therein; and,
- one or more walls.

6. An assembly for generating energy from waves, comprising:

- a concentric ring flywheel operatively arranged to interact with at least one stator for generating electrical current, the concentric ring flywheel comprising:
 - a first shaft including an input end and an output end;
 - a plurality of rings, the plurality of rings including at least:
 - a first ring, including: a first radially inward facing surface arranged to connect with the output end of the first shaft; and,
 - a first radially outward facing surface;
 - a second ring arranged concentrically around the first ring, the second ring including:
 - a second radially inward facing surface; and,
 - a second radially outward facing surface, wherein a first space is arranged radially between the first radially outward facing surface and the second radially inward facing surface; one or more first clutch connectors arranged in the first space to non-rotatably connect the second ring and the first ring; and,
 - a wave energy capture device operatively arranged to rotate the first shaft,

wherein:

- when the first ring rotates at a first rotational speed, the first ring and the second ring are rotatable with respect to each other; and,
- when the first ring rotates at a second rotational speed, the one or more first clutch connectors non-rotatably connect the first ring and the second ring.

7. The assembly as recited in claim 6, wherein at least one of the plurality of rings is hollow and comprises fluid therein.

8. The assembly as recited in claim 6, wherein at least one of the plurality of rings is hollow and comprises:

- fluid arranged therein; and,
- one or more ridges.

9. The assembly as recited in claim 6, wherein at least one of the plurality of rings is hollow and comprises:

- fluid arranged therein; and,
- one or more walls.

10. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

- a wave chamber arranged to engage a body of water comprising a plurality of waves, including:
 - a floor having a front end and a rear end;
 - a first opening arranged proximate the front end;
 - a second opening arranged proximate the rear end; and,
 - a hose arranged on said floor and extending from the first opening to the second opening, the hose operatively arranged to continuously fill with water from the body of water;

a cylinder arranged on said floor proximate the front end, the cylinder connected to the wave chamber via one or more springs;

a cistern fluidly connected to the hose; and,

a turbine fluidly connected to the cistern and non-rotatably connected to the input end of the first shaft; wherein, when one of the plurality of waves enters the first opening, the cylinder:

is displaced along the floor from the front end to the rear end; and,

expresses the water in the hose into the cistern.

11. The assembly as recited in claim 9, wherein the water in the cistern flows through the turbine to rotate the first shaft and the first ring.

12. The assembly as recited in claim 9, wherein the hose comprises one or more one-way valves.

13. The assembly as recited in claim 9, further comprising a wave gate operatively arranged proximate the front end to regulate the magnitude of the plurality of waves.

14. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

a float operatively arranged to engage a body of water comprising a plurality of waves;

a wheel connected to the input end of the first shaft;

a second shaft comprising a first end connected to the float and a second end connected to the wheel; and,

a fulcrum arranged to engage the second shaft at a point between the first and second ends;

wherein, when the plurality of waves displace the float:

the second shaft oscillates and rotates the wheel; and,

the wheel rotates the first shaft and the first ring.

15. The assembly as recited in claim 14, further comprising:

a third shaft comprising a third end non-rotatably connected to the wheel and a fourth end; and,

a gearbox connected to the fourth end and non-rotatably connected to the input end of the first shaft;

wherein, when the plurality of waves displace the float:

the second shaft oscillates and rotates the wheel;

the wheel rotates the third shaft; and,

the gearbox rotates the first shaft the first ring.

16. The assembly as recited in claim 14, further comprising an oscillation restrictor operatively arranged to engage the second shaft at a point between the first and second ends.

17. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

a float operatively arranged to engage a body of water comprising a plurality of waves;

a second shaft, comprising:

a first end connected to the float; and,

a second end connected to the input end of the first shaft, wherein the first shaft comprises external threading operatively arranged to engage internal threading on the first radially inward facing surface; and,

a fulcrum arranged to engage the second shaft at a point between the first and second ends;

wherein, when the plurality of waves displace the float:

the second shaft oscillates and displaces the first shaft with respect to the concentric ring flywheel; and,

the external threading engages the internal threading to rotate the first ring.

18. The assembly as recited in claim 17, further comprising an oscillation restrictor operatively arranged to engage the second shaft at a point between the first and second ends.

19. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

one or more pump segments operatively arranged to engage a body of water comprising a plurality of waves, each of said one or more pump segments including:

a first end;

a second end;

a lateral wall extending between the first and second ends;

a piston arranged within the lateral wall forming a chamber;

an inlet valve arranged on the lateral wall; and,

an outlet valve arranged on the lateral wall;

a hose fluidly connected to the outlet valve;

a cistern fluidly connected to the hose; and,

a turbine fluidly connected to the cistern and non-rotatably connected to the input end of the first shaft;

wherein when the piston displaces:

in a first direction, water enters the chamber through the inlet valve;

in a second direction, opposite the first direction, the water is forced out of the chamber through the outlet valve, through the hose and into the cistern.

20. The assembly as recited in claim 19, wherein each of the one or more pump segments further comprises:

a spring connecting the piston to the first end; and,

at least one cord connecting the piston to one of an adjacent pump segment, float, or fixed object arranged proximate the second end;

wherein:

as the pump segment pivots from a relaxed state to a flexed state, the cord displaces the piston in the second direction; and,

as the pump returns from the flexed state to the relaxed state, the spring displaces the piston in the first direction.

21. The assembly as recited in claim 20, wherein each of the one or more pump segments further comprises a pulley connected to the second end, wherein the at least one cord engages the pulley.

22. The assembly as recited in claim 19, wherein the water in the cistern flows through the turbine to rotate the first shaft and the first ring.

23. The assembly as recited in claim 19, wherein the hose comprises one or more one-way valves.

24. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

a wave fan operatively arranged to engage a body of water comprising a plurality of waves or currents;

a second shaft, comprising:

a first end connected to the wave fan;

a second end; and,

a pivot arranged at a point between the first and second ends;

a roller connected to the second end;

a hose operatively arranged to continuously fill with water from the body of water;

a cistern fluidly connected to the hose; and,

a turbine fluidly connected to the cistern and non-rotatably connected to the input end of the first shaft;

wherein when one of the plurality of waves or currents displaces the wave fan in a first circumferential direction, the roller:

engages the hose; and,

expresses the water in the hose into the cistern.

25. The assembly as recited in claim 24, wherein the water in the cistern flows through the turbine to rotate the first shaft and the first ring.

29

26. The assembly as recited in claim 24, wherein the hose comprises one or more one-way valves.

27. The assembly as recited in claim 6, wherein the wave energy capture device comprises:

a wave fan operatively arranged to engage a body of water comprising a plurality of waves or currents;

a second shaft, comprising:

a first end connected to the wave fan; and,

a second end rotatably connected to a pivot;

a rotor having one or more protrusions, the rotor connected to the second end;

a hose operatively arranged to continuously fill with water from the body of water;

a cistern fluidly connected to the hose; and,

a turbine fluidly connected to the cistern and non-rotatably connected to the input end of the first shaft;

wherein when one of the plurality of waves or currents displaces the wave fan in a first circumferential direction:

the rotor rotates in the first circumferential direction;

and,

30

the one or more protrusions engage the hose and express the water in the hose into the cistern.

28. The assembly as recited in claim 27, wherein the rotor comprises a ratchet mechanism which, when engaged, allows the rotor to rotate only in the first circumferential direction.

29. The assembly as recited in claim 28, wherein the ratchet mechanism comprises:

a ratchet rotatably connected to the second end and the pivot, the ratchet including a plurality of teeth;

a pawl arranged to engage the plurality of teeth; and,

a catch rotatably connected to the second shaft and arranged to engage the plurality of teeth.

30. The assembly as recited in claim 27, wherein the water in the cistern flows through the turbine to rotate the first shaft and the first ring.

31. The assembly as recited in claim 27, wherein the hose comprises one or more one-way valves.

* * * * *